

Reliable plug-and-play 44-inch small team printer






#### Easily do more in less time and grow your business

- Get the job done quickly without sacrificing quality thanks to this printer's fast (Economode) print setting-2 A1/D-sized prints per minute.
- Improve your media loading with a convenient, hassle-free front-loading top roll printer, and save time with alerts that facilitate timely replacement.
- Small teams can share this printer thanks to its built-in network card.
- Increase your possibilities with system enhancements like more memory and optional PostScript accessory.(1
- Print batch HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, PowerPoint) files easily—without opening any application—thanks to the free HP Instant Printing Utility and the embedded Web server.



#### Small details increase your power to communicate


- Achieve rich, dark blacks and fine detailed lines with HP Vivera inks, including 2 HP Vivera blacks and a gray ink in this 6-ink printing system.
- Produce exacting detail with 0.02 mm (0.0008 in) minimum line width, (2 and highly accurate drawings with 0.1% line accuracy.
- Easily create stunning large-format posters that convey your message loud and clear with the optional Serif PosterDesigner Pro for HP.(3



Optimize blueprints—use this printer's new printing mode for generic natural tracing paper.

#### Focus on your design with a reliable printer

- Work with confidence knowing this printer can easily process complex files.
- Increase your memory capabilities with a 160 GB hard disk version printer, including 8 GB of dedicated memory for fast file processing.<sup>(4)</sup>
- Experience greater operating system support with original HP-GL/2 and RTL.
- Experience efficient, reliable printing with Original HP printing supplies and printing materials.
- · Manage your printer fleet and costs with HP Web Jetadmin, embedded Web server and the HP accounting tool.





HP DESIGNJET T770 PRINTER

- Save paper with blank print area detection, image auto-rotate and realistic
- Less ink wasted thanks to efficient installation and maintenance routines
- Free, convenient cartridge and printhead recycling<sup>(1)</sup> Supports 100% recycled HP media
- ENERGY STAR® Qualified Product















- The PostScript accessory is an optional accessory to be purchased separately (includes 6 GB memory upgrade).
- Serif PosterDesigner Pro for HP is an optional software accessory to be purchased separately.
- 8 GB maximum memory includes 2 GB of standard memory and an optional 6 GB memory accessory, which must be purchased separately.

# **HP DESIGNJET T770**

## PRINTER SERIES

#### **TECHNICAL SPECIFICATIONS**

Line drawings <sup>(2</sup>	Fast: 28 sec/page on A1/D, 103 A1/D prints per hour
Color images	Fast: 51 m²/hr (549 ft²/hr) ²
•	Best: 3.1 m²/hr (33.3 ft²/hr) 3
Printing	
Print resolution	Up to 2400 x 1200 optimized dpi
Margins	<b>Roll:</b> 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in)
(top x bottom x left x right)	Sheet: 5 x 16.75 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in)
Technology	HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK); pigment-based (MK)
Ink colors	Cyan, gray, magenta, matte black, photo black, yellow
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
Ink cartridge size	130 ml (cyan, gray, magenta, matte black, photo black, yellow)
	69 ml (cyan, gray, magenta, photo black, yellow)
Printheads	3 (matte black and yellow, magenta and cyan, gray and photo black)
Line accuracy Minimum line width	+/- 0.1% <sup>4</sup>
Guaranteed minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
Maximum print length	0.06 mm (0.0024 in) (ISO/IEC 13660:2001(E)) <sup>15</sup> 91 m (300 ft) (OS and application dependent)
Media	71 III (300 II) (C3 diid application dependerii)
Handling	Sheet feed; roll feed; automatic cutter
Types	Bond and coated papers, technical papers, films, photographic papers, backlit
Types	materials, self-adhesive materials
Weight	60 to 328 g/m <sup>2</sup>
Size	210 x 279 to 1118 x 1676 mm (8.26 x 11 to 44 x 66 in) sheets; 27.94 to
	111.76 cm (11 to 44 in) rolls
Thickness	Up to 11.8 mil
Memory	
	Base Model: 2 GB dedicated file-processing memory
	Hard Disk Version Printer: 8 GB dedicated file processing memory, 160 GB hard
	disk
Connectivity	1. [ [ ]   [
Interfaces (standard)	1 Fast Ethernet (100Base-T) port, 1 Hi-Speed USB 2.0 certified port, 1 EIO
Interfaces (entined)	Jetdirect accessory slot
Interfaces (optional) Print languages (standard)	HP Jetdirect EIO print servers  Base model: HP-GL/2, HP-RTL, HP PCL 3 GUI
i iiii iunguuges (sianaara)	
Drint languages /!IV	Hard Disk Version Printer: HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI  Adobe® PostScript® 3™, Adobe PDF 1.7 (with optional PostScript Upgrade
Print languages (optional)	accessory)
Drivers (included)	HP-GL/2, HP-RTL drivers for Windows® (optimized for AutoCAD 2000 and higher);
	HP PCL 3 GUI driver for Mac OS X; support for Citrix XenApp and Citrix XenServer
	environments; PostScript Windows, Linux, and Mac drivers with optional dongle (will
	remove HP PCL 3 GUI driver support)
Recommended system requirem	
Mac	Mac OS X v 10.4, Mac OS X v 10.5: PowerPC G4, G5, or Intel Core Processor; 1
) A C	GB RAM; 2 GB available hard disk space
Windows	Windows XP® (SP2 or later): Intel® Pentium® family or AMD® K6/Athlon/Duron family (1 GHz), 1 GB RAM, 2 GB available hard disk space; Windows Vista®:
	idilily (1 GHz), 1 GB KAM, 2 GB dvalidble lidid disk space, vvilidows visid .
	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard
Dimensions (w x d x h)	
Dimensions (w x d x h) Printer	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)
	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space
Printer Shipping Weight	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)
Printer Shipping Weight Printer	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)
Printer Shipping Weight Printer Shipping	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)
Printer Shipping Weight Printer	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)
Printer Shipping Weight Printer Shipping	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in
Printer Shipping Weight Printer Shipping	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster,
Printer Shipping Weight Printer Shipping What's in the box	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in
Printer Shipping Weight Printer Shipping	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster,
Printer Shipping Weight Printer Shipping What's in the box Environmental ranges	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating lemperature	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating Recommended operating Recommended operating	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  1111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby	32bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A)  26 dB(A)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 1111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 6.2 B(A)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, active	32bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A)  26 dB(A)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound pressure, standby Sound power, standby Sound power, standby Power consumption	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A)  26 dB(A)  6.2 B(A)  4.4 B(A)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Maximum	32bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 1111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 6.2 B(A) 120 watts
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage temperature Storage temperature Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave	32bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.2 B(A) 120 watts  < 7 watts (< 25 watts with embedded DFE)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A)  26 dB(A)  4.4 B(A)  120 watts  < 7 watts (< 25 watts with embedded DFE)  0.1 watts
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage temperature Storage temperature Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 1111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A)  120 watts  < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz),
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating lemperature Recommended operating temperature Storage lemperature Recommended operating humidity Storage lemperature Sound pressure, standby Sound power, active Sound pressure, standby Sound power, active Osund power, active Sound power, active Osund power consumption Maximum Powersave Off	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A)  26 dB(A)  4.4 B(A)  120 watts  < 7 watts (< 25 watts with embedded DFE)  0.1 watts
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, atandby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)  1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb)  111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power code  5 to 40° C (41 to 104° F)  15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F)  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A)  26 dB(A)  4.4 B(A)  120 watts  < 7 watts (< 25 watts with embedded DFE)  0.1 watts  Input voltage (auto ranging) 100 to 240 VAC (+/-10%), 50/60 Hz (+/-3 Hz), 2 A max
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating lemperature Recommended operating temperature Storage lemperature Recommended operating humidity Storage lemperature Sound pressure, standby Sound power, active Sound pressure, standby Sound power, active Osund power, active Sound power, active Osund power consumption Maximum Powersave Off	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 1111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A)  120 watts  < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max  USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, atandby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.2 B(A) 4.4 B(A)  120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max  USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating lemperature Recommended operating temperature Storage lemperature Recommended operating temperature Storage lemperature Storage humidity Storage humidity Storage humidity Storage numidity Sound power, active Sound pressure, standby Sound power, active Sound pressure, active So	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.4 B(A)  120 watts 120 watts 120 watts 121 watts 122 max  USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating lemperature Recommended operating temperature Storage lemperature Recommended operating temperature Storage lemperature Storage humidity Storage humidity Storage humidity Storage numidity Sound power, active Sound pressure, standby Sound power, active Sound pressure, active So	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.4 B(A)  120 watts 120 watts 120 watts 121 watts 122 max  USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage temperature Sound pressure, active Sound pressure, standby Sound power, active Sound pressure, standby Power consumption Maximum Powersave Off Power requirements  Certification Safety  Electromagnetic	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.4 B(A)  120 watts  170 watts 180 kg (25 watts with embedded DFE) 181 kg (25 watts with embedded DFE) 182 kg (25 watts with embedded DFE) 183 card Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japa (VCCI); Certified as Class A product: Korea (KCC) WEEE, EU RoHS, China RoHS, REACH, Eup, FEMP
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, standby Fower consumption Maximum Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic Environmental Enversory Environmental	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max  USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (FSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)
Printer Shipping Weight Printer Shipping What's in the box  Environmental ranges Operating lemperature Recommended operating temperature Storage lemperature Recommended operating temperature Storage lemperature Storage humidity Storage humidity Storage humidity Storage numidity Sound power, active Sound pressure, standby Sound power, active Sound pressure, active So	32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in) 1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)  81.6 kg (180 lb) 111 kg (244 lb)  Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)  -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A) 26 dB(A) 4.4 B(A)  120 watts  1 20 watts 1 20 watts 1 20 watts 1 20 watts 1 20 watts 1 20 watts 1 20 watts 1 20 max  USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES) EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) WEEE, EU RoHS, China RoHS, REACH, Eup, FEMP

#### ORDERING INFORMATION

ORDERING INFORMATION		
Product		
CH539A	HP Designjet T770 44-in Printer	
CN375A	HP Designjet T770 44-in Hard Disk Version Printer	
Accessories		
Q6709A	HP Designjet 44-inch Roll Feed Spindle	
CN500A	HP Designjet T770 PostScript Upgrade	
CN499A	HP Designjet T770 Memory Upgrade	
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server	
CN088A	Serif PosterDesigner Pro for HP	
Original HP printheads		
C9380A	HP 72 Gray and Photo Black Printhead	
C9383A	HP 72 Magenta and Cyan Printhead	
C9384A	HP 72 Matte Black and Yellow Printhead	
Original HP in		
C9397A	HP 72 69-ml Photo Black Ink Cartridge	
C9398A C9399A	HP 72 69-ml Cyan Ink Cartridge HP 72 69-ml Magenta Ink Cartridge	
C9400A	HP 72 69-ml Yellow Ink Cartridge	
C9401A	HP 72 69-ml Gray Ink Cartridge	
C9403A	HP 72 130-ml Matte Black Ink Cartridge	
C9370A	HP 72 130·ml Photo Black Ink Cartridge	
C9371A	HP 72 130-ml Cyan Ink Cartridge	
C9372A	HP 72 130·ml Magenta Ink Cartridge	
C9373A	HP 72 130-ml Yellow Ink Cartridge	
C9374A	HP 72 130-ml Gray Ink Cartridge	
Original HP p	rinting materials	
Q6627A	HP Super Heavyweight Plus Matte Paper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m	
Q6628A	HP Super Heavyweight Plus Matte Paper 210 g/m², 42 in. x 100 ft/1067 mm x 30,5 m	
C6030C	HP Heavyweight Coated Paper 131 g/m², 36 in. x 100 ft/914 mm x 30,5 m	
C6569C	HP Heavyweight Coated Paper 131 g/m², 42 in. x 100 ft/1067 mm x 30,5 m	
Q1956A	HP Heavyweight Coated Paper 131 g/m², 42 in. x 225 ft/1067 mm x 67,5 m (NA & EMEA only)	
C6019B	HP Coated Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m	
C6020B	HP Coated Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m	
C6980A	HP Coated Paper 90 g/m², 36 in. x 300 ft/914 mm x 91,4 m	
C1860A	HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology	
C6035A	HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (EMEA & AP only)	
COOOSA	now with ColorPRO Technology	
C1861A	HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only)	
	now with ColorPRO Technology	
C6036A	HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only)	
	now with ColorPRO Technology	
C6810A	HP Bright White Inkjet Paper 90 g/m², 36 in. x 300 ft/914 mm x 91,4 m	
014454	now with ColorPRO Technology	
Q1445A	HP Bright White Inkjet Paper 90 g/m², (A1) 23.39 in. x 150 ft/594 mm x 45,7 m (EMEA & JP only) now with ColorPRO Technology	
Q1397A	HP Universal Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with ColorPRO Technology	
C3868A	HP Natural Tracing Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m	
C3875A	HP Clear Film 174 g/m², 36 in. x 75 ff/914 mm x 22,9 m	
51642B	HP Matte Film 160 g/m², 36 in. x 125 ft/914 mm x 38,1m	
Q1427A	HP Universal High-gloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only)	
Q1421A	HP Universal Semi-gloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only)	
CG459A	HP Premium Matte Photo Paper 210 g/m², 24 in. x 100 ft/610 mm x 30,5 m	
CG460A	HP Premium Matte Photo Paper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m	
C7960A	HP Reverse Print Matte Backlit Film 160 g/m², 36 in. x 75 ft/914 mm x 22,9 m (NA, EMEA, AP only)	
Q8834A	HP Self-adhesive Gloss Polypropylene 120 g/m², 36 in. x 75 ft/914 mm x 22,9 m	
Q1442A	HP Coated Paper 90 g/m², (A1) 23.39 in. x 150 ft/594 mm x 45,7 m (EMEA & JP only)	
CG886A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 24 in. x 100 ft/610 mm x 30,5 m (US & EMEA only)	
CG887A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 100 ft/914 mm x 30,5 m (US & EMEA only)	
CG888A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in. x 100 ft/1067 mm x 30,5 m (US & EMEA only)	
CG883A	HP Cockle-free Coated Paper 100 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only)	
CG884A	HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only)	
CG885A	HP Cockle-free Coated Paper 100 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only)	
CG889A	HP Recycled Bond Paper 80 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper	
CG890A	HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only)	
	made of 100% recycled base paper	
CG891A	HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only)	
	made of 100% recycled base paper	
CG892A	HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only)	
	made of 100% recycled base paper	
Service and su		
US251E	3 year, Next business day, Onsite Support	
US249E	5 year, Next business day, Onsite Support 4 year, Next business day, Onsite Support	
US250E		
US244E US245PE	3 year, 4 hour response 13 by 5 Onsite Support  1 year, Post Warranty, Next business day, Onsite Support	
US239PE	1 year, Post Warranty, Next business day, Onsite Support  1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support	
H4518E	Installation and Network Configuration	
	· ·-···g-·-··	

For more HP large-format printing materials and sizes please visit us online at: www.hp.com/go/designjet/supplies

- Mechanical printing time

- Mechanical printing time
  Printed on plain media with Economode on
  Printed on glossy media
  +/-0.1% of the specified vector length or +/-0.1 mm (whichever greater) at 23° C (73° F), 50-60% relative
  humidity, on E/AO printing material in Best or Normal mode with HP Matte Film
  Measured on HP Matte Film

## FOR MORE INFORMATION, VISIT OUR WEBSITE AT

## WWW.HP.COM/GO/DESIGNJETT770

© Copyright 2009 Hewlett-Packard Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe PostScript 3 is a trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AMD is a trademark of Advanced Micro Devices, Inc. Intel and Pentium are trademarks of Intel Corporation in the U.S. and other countries. Windows, Windows XP, and Windows Vista are U.S. registered trademarks of Microsoft Corporation.

