

# HP Designjet T1200 Printer series

Achieve twice the productivity with two printers in one for medium-sized CAD/GIS workgroups.





### Get more done in less time with fast setup, continuous printing and network sharing.

- Manage tight deadlines easily: print 2 A1-sized prints per minute using the Economode print setting
- Save time and paper with 2 online rolls and smart switching, enabling unattended printing
- Print continuously with reliable HP 300-ml matte black ink cartridges, a convenient front-loading top roll and media length tracking
- Print batch files<sup>2</sup> without opening any application thanks to the free HP Instant Printing Utility and embedded Web server
- Enjoy easy sharing with a built-in network card



## Make a real impact with clear, accurate drawings and colourful presentations.

- Reach a new level of accuracy and professionalism: achieve fine lines, rich dark blacks, true neutral greys and a range of vivid colours with HP Vivera inks and the 6-ink printing system
- Achieve exacting detail with 0.02 mm minimum line width<sup>3</sup> and highly precise drawings with 0.1% line accuracy
- Create great prints with new, improved HP bond papers and HP Recycled Bond Paper (100% recycled base paper)
- Optimise blue prints using the new printing mode for generic natural tracing paper

#### Print confidently with this reliable and secure solution

- Process complex files fast and accurately, with 32 GB of memory
- Free your network and workstation with reliable in-printer processing architecture
- Share this HP Designjet among authorised workgroups using built-in Gigabit Ethernet networking and Jetdirect support for secure IPsec and IPv6
- Secure disk erase and the external hard disk accessory<sup>4</sup> provide even more security
- Do more with PostScript capabilities and experience greater operating system support with original HP-GL/2 and RTL























<sup>1</sup> With two rolls in one device, you achieve twice the productivity from a single printer.

 $<sup>2~\</sup>mbox{HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, Powerpoint)}$ 

<sup>3</sup> HP-GL/2 addressable

<sup>4</sup> The 160 GB external hard disk drive accessory is an optional accessory; please purchase separately; this accessory is intended to replace the printer's internal hard disk as the repository of personal data, and can be removed from the printer and stored in a secure place

#### HP Designjet T1200 Printer series

Print speed	Fast: 28 sec/page 103 A1 prints per hour
Line drawings Printing	Fast: 28 sec/page, 103 A1 prints per hour
Print resolution	Up to 2400 x 1200 optimised dpi
Margins (top x bottom x left x right)	Roll: 5 mm (top), 5 mm (right), 5 mm (left), 5 mm (bottom) Sheet: 5 mm (top), 5 mm (right), 5 mm (left), 16.75 mm (bottom)
Technology	HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK), pigment-based (MK)
Ink colours	6 (cyan, grey, magenta, matte black, photo black, yellow)
Ink drop Line accuracy	6 pl (C, M, PK, G), 9 pl (Y, MK) +/- 0.1% (+/-0.1% of the specified vector length or +/-0.1 mm - whichever
Line accordey	greater - ot 23° C, 50-60% relative humidity, on A0 printing material in Best or Normal mode with HP Matte Film)
Minimum line width	0.02 mm (HP-GL/2 addressable)
Guaranteed minimum line width	0.06 mm (ISO/IEC 13660:2001(E))
Maximum print length  Image quality	91 m (OS and application dependent)
Maximum optical density	2.15 maximum black optical density (6 L *min)
Media	
Handling	Sheet feed, two automatic roll feeds, automatic roll-switching, automatic cutter
Types	Bond and coated paper, technical paper, film, photographic paper, backlit self-adhesive
Weight Size	60 to 328 g/m <sup>2</sup> 210 x 279 to 1118 x 1676 mm
Thickness	Up to 0.8 mm
Memory	
Standard	32 GB
Hard disk	Standard, 160 GB
Connectivity Interfaces (standard)	1 Gigabit Ethernet (1000Base-T) port; 1 Hi-Speed USB 2.0 certified port; 1 EIO Jetdirect accessory slot
Interfaces (optional)	HP Jetdirect internal print servers
Print languages (standard)	T1200 PS 1118 mm: Adobe PostScript® 3, Adobe PDF 1.7, TIFF, JPEG, HP.GL/2, HP.RTL, CALS G4, HP PCL 3 GUI; T1200 1118 mm: HP.GL/2, HP.RTL, CALS G4, HP PCL 3 GUI;
Drivers included	HP.GL/2, HP.RTL, Postscript drivers for Windows® (optimised for AutoCAD 2000 and higher); HP PCL 3 GUI, Postscript drivers for Mac OS X and Linux; support for Citrix XenApp and Citrix XenServer environments). Postscript and Linux drivers only supported through CK834A.
Recommended system requirements	Tosiscripi and Emox anvers only supported imough excours.
Mac	Mac OS X v10.4, v10.5: PowerPC G4, G5, or Intel® Core Processor; 1 GB RAM; 2 GB available hard disk space
Windows	Microsoft® Windows® XP Home/Professional (SP2 or higher): Intel® Pentium® family or AMD K6®/Athlon™/Duron™ family (1 GHz), 1 GB RAM, 2 GB available hard disk space; Windows Vista® Home
	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1
Dimensions (w x d x h)	
Dimensions (w x d x h) Printer	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm
Printer Shipping	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space
Printer Shipping Weight	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm
Printer Shipping Weight Printer	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm
Printer Shipping Weight Printer Shipping What's in the box	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg
Printer Shipping Weight Printer Shipping	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif
Printer Shipping Weight Printer Shipping What's in the box CK834A	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif
Printer Shipping Weight Printer Shipping What's in the box CK834A CH538A	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118
Printer Shipping Weight Printer Shipping What's in the box	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif
Printer Shipping Weight Printer Shipping What's in the box CK834A CH538A Environmental ranges	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)  46 dB(A), 26 dB(A) (standby)  6.2 B(A), 4.4 B(A) (standby)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A), 26 dB(A) (standby)  6.2 B(A), 4.4 B(A) (standby)  120 watts maximum (active), < 27 watts (standby), < 7 watts / < 25 watts with embedded DFE (powersave), 0.1 watts (off)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A), 26 dB(A) (standby)  6.2 B(A), 4.4 B(A) (standby)  120 watts maximum (active), < 27 watts (standby), < 7 watts / < 25 watts
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Pressure Sound Power Power Consumption Maximum  Power requirements  Certification	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A), 26 dB(A) (standby)  6.2 B(A), 4.4 B(A) (standby)  120 watts maximum (active), < 27 watts (standby), < 7 watts / < 25 watts with embedded DFE (powersave), 0.1 watts (off)  Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum Power requirements  Certification Safety	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg 115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C 15 to 35° C (depending on paper type) 25 to 55° C 20 to 80% RH (depending on paper type) 0 to 95% RH  46 dB(A), 26 dB(A) (standby) 6.2 B(A), 4.4 B(A) (standby)  120 watts maximum (active), < 27 watts (standby), < 7 watts / < 25 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max  EU (IVD and EN 60950-1 compliant), Russia (GOST)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Pressure Sound Power Power Consumption Maximum  Power requirements  Certification	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg  115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C  15 to 40° C  15 to 35° C (depending on paper type)  25 to 55° C  20 to 80% RH (depending on paper type)  0 to 95% RH  46 dB(A), 26 dB(A) (standby)  120 watts maximum (active), < 27 watts (standby), < 7 watts / < 25 watts with embedded DFE (powersave), 0.1 watts (off)  Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max  EU (IVD and EN 60950-1 compliant), Russia (GOST)  Compliant with Class B requirements EU (EMC Directive)
Printer Shipping Weight Printer Shipping What's in the box CK834A  CH538A  Environmental ranges Operating Temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum Power requirements  Certification Safety Electromagnetic	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space  1770 x 722 x 1050 mm  1930 x 766 x 778 mm  86 kg 115 kg  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  Printer, printheads (3 x 2 colours each), introductory ink cartridges, 1118 mm stand, 1118 mm spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord  5 to 40° C 15 to 35° C (depending on paper type) 25 to 55° C 20 to 80% RH (depending on paper type) 0 to 95% RH  46 dB(A), 26 dB(A) (standby) 6.2 B(A), 4.4 B(A) (standby)  120 watts maximum (active), < 27 watts (standby), < 7 watts / < 25 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max  EU (IVD and EN 60950-1 compliant), Russia (GOST)

#### ORDERING INFORMATION

Product	
CK834A	HP Designjet T1200 1118 mm PostScript Printer
CH538A	HP Designjet T1200 1118 mm Printer
Accessories	
Q6709A	HP Designjet 1118mm Roll Feed Spindle
CN501A	HP Designjet External Hard Disk
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
CN088A	Serif PosterDesigner Software Pro for HP Designjet Printers
CN454A	SCP reprocontrol for HP (1 printer)
CN455A	SCP reprocontrol for HP (2 printers)
Ink supplies	
C9397A	HP 72 69-ml Photo Black Ink Cartridge
C9398A	HP 72 69-ml Cyan Ink Cartridge
C9399A	HP 72 69-ml Magenta Ink Cartridge
C9400A	HP 72 69-ml Yellow Ink Cartridge
C9401A	HP 72 69-ml Grey Ink Cartridge
C9403A	HP 72 130-ml Matte Black Ink Cartridge
C9370A	HP 72 130-ml Photo Black Ink Cartridge
C9371A	HP 72 130-ml Cyan Ink Cartridge
C9372A	HP 72 130-ml Magenta Ink Cartridge
C9373A	HP 72 130-ml Yellow Ink Cartridge
C9374A	HP 72 130-ml Grey Ink Cartridge
CH575A	HP 726 300-ml Matte Black Designjet Ink Cartridge
C9380A	HP 72 Gray and Photo Black Printhead
C9383A	HP 72 Magenta and Cyan Printhead
C9384A	HP 72 Matte Black and Yellow Printhead
Media supplies	
Q6628A	HP Super Heavyweight Plus Matte Paper-1067 mm x 30.5 m (42 in x 100 ft)
C6030C	HP Heavyweight Coated Paper-914 mm x 30.5 m (36 in x 100 ft)
C6020B	HP Coated Paper-914 mm x 45.7 m (36 in x 150 ft)
C6036A	HP Bright White Inkjet Paper-914 mm x 45.7 m
Q1397A	HP Universal Bond Paper-914 mm x 45.7 m (36 in x 150 ft)
CG891A	HP Recycled Bond Paper-1067 mm x 45.7 m (42 in x 150 ft)
C3868A	HP Natural Tracing Paper-914 mm x 45.7 m (36 in x 150 ft)
C3875A	HP Clear Film-914 mm x 22.9 m (36 in x 75 ft)
Q1421A	HP Universal Semi-gloss Photo Paper-914 mm x 30.5 m (36 in x 100 ft)
Q1427A	HP Universal High-gloss Photo Paper-914 mm x 30.5 m (36 in x 100 ft)
Service & support	

US235E HP Care Pack, Next Business Day On Site, 5 years
US236E HP Care Pack, Next Business Day On Site, 4 years
US237E HP Care Pack, Next Business Day On Site, 3 years
US230E HP Care Pack, 4hr 13x5 Same Business Day On Site, 3 years
US230E HP Care Pack, Post Warranty, Next Business Day On Site, 1 year
US23PE HP Care Pack, Post Warranty, Next Business Day On Site, 1 year

For more HP Large Format Media substrates and sizes please visit us online at: http://www.hp.com/go/designjet/supplies

For more information, visit our website at http://www.hp.com

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA2-8299EEE Published in EMEA January 2011

