

F-Series Filters & Filter Regulators

A030_0918

Piggyback filters & filter regulators



FR250-G



FR500-G

Features

- ¼" (FR250-G) or ½" (FR500-G)
- Adjustable 0-120 PSI regulator
- Filter/Regulator with glass face chrome gauge
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Filters to 5 micron
- Max. pressure is 230 PSI (FR250-G) / 180 PSI (FR500-G)
- Temperature range from 40° F to 120° F
- 30 SCFM (FR250-G) & 80 SCFM (FR500-G) rating

***Provides CLEAN AIR to your applications at a LOW COST!
Perfect for DIY-ERS & SMALL SHOPS***



F250



F500

Features

- ¼" (F250) or ½" (F500)
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Lightweight, high efficiency design is durable and rugged
- Filters to 5 micron
- Maximum pressure is 230 PSI (F250) / 180 PSI (F500)
- Temperature range from 40° F to 120° F
- 30 SCFM (F250) and 80 SCFM (F500) rating

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

