

Industrial 2U Rackmount -Active PFC- SS-600H2U Active PFC



www.seasonic.com



Features:

- Specification compliance: Intel EPS2U v2.1 and ATX12V v2.2
- Forward converter circuit
- High efficiency and reliability for industrial level
- Easy swap connector design
- High reliability ball bearing fan
- Low ripple & noise
- Smart & Silent Fan Control (S²FC)
- Short circuit protection on all outputs
- Over voltage protection
- Over power protection
- 100% hi-pot test
- 100% burn in, high temperature cycled on/off
- PFC harmonics compliance: IEC1000-3-2 /EN61000-3-2 standards

DC Outputs:

Model	DC Outputs					Total power	Input type
	+3.3V	+5V	+12V Combined	-12V	+5Vsb		
SS-600H2U Active PFC	20A	25A	45A	0.8A	3A	600W	Full range
	150W		540W				

Electrical Specifications:

- Input frequency: 50 / 60 Hz
- Inrush current, cold start: 100A max.
- Hold up time, full load: 16ms. typical
- Efficiency, 220-240VAC, full load: 83% typical
- Efficiency, 100-120VAC, full load: 80% typical
- Dielectric withstand, input to frame/ ground: 1800VAC, 1sec.
- Dielectric withstand, input to output: 1800VAC, 1sec.
- Line regulation: +/--1% typical
- Load regulation: +/--5% typical
- Cross regulation: +/--5% typical
- Ripple / noise: 1%
- MTBF, full load@25°C amb. : >100K hours
(Excluding the DC fan)
- Power Factor Correction: Active PFC 99% typical

Safety: CUL, TUV, CB, CCC

EMC: CE, FCC

Specification may change without prior notice

Dimension: L270 x W100 x H70mm
(10.6" x 3.9" x 2.7")

Fan type: 60 x 60mm

Connectors:

Customized modular cables

Sea Sonic Electronics Co., Ltd.
www.seasonic.com
sales@seasonic.com.tw
Tel: +886 2 2659 0338
Fax: +886 2 2659 0530

Seasonic Electronics Inc.
www.seasonicusa.com
usa@seasonic.com
Tel: +1 626 969 9966
Fax: +1 626 969 9986

Sea Sonic Europe B.V.
europe@seasonic.com
Tel: +31 (0)10-2262131
Fax: +31 (0)10-2266689

