



The 15.6" LED-backlit ProLite T1634MC uses Projective Capacitive Multi-Touch Technology. It is built into an eye catching bezel with Edge to Edge glass. The screen features a 1366 x 768 resolution, DVI and VGA input. A rugged bezel and IP54 rated front make it suitable for demanding environments. The ProLite T1634MC is the ideal solution for Instore Retail and Kiosks.

1. DISPLAY CHARACTERISTICS

DIAGONAL	15.6"; 39.5cm
TOUCHTECHNOLOGY	projective capacitive, multitouch (2 compatible touch points - HID, supported only under Windows® 7/8), activated by finger
PANEL	TN LED-backlit
GLASS HARDNESS	7H minimum
DISPLAY AREA H X W	193.5 x 344.2 mm; 7.6" x 13.6"
RESPONSE TIME	8 ms
CONTRAST	500 : 1 with touch panel
BRIGHTNESS	225 cd/m ² with touch panel
VIEWING ZONE	horizontal/vertical: 90° / 65°; right/left: 45° / 45°; up/down: 30° / 35°
DISPLAY COLOUR	16.7 million
PIXEL PITCH H X V	0.252 x 0.252 mm
NATIVE RESOLUTION	1366 x 768 (1.0 megapixel)
HORIZONTAL SYNC	31.4 - 60.3 KHz
VERTICAL SYNC	56 - 75 Hz
SYNCHRONIZATION	Separate Sync
ASPECT RATIO	16 : 9
LIGHT TRANSMITTANCE	90%

2. INTERFACES & CONNECTORS

ANALOG INPUT CONNECTOR	VGA
DIGITAL INPUT CONNECTOR	DVI-D
INPUTS	USB (for touch connectivity)

3. SPECIAL FEATURES

PLUG & PLAY	VESA DDC2B™
CONTROLS	On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Contrast, Select/ Auto, Power)
USER CONTROLS	contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, OSD language, colour temperature
ANTI-THEFT-DEVICE	Kensington-lock™ prepared
SAFETY	CE, TÜV-Bauart, VCCI, IP54 (front)
TILT ANGLE	90° up; 5° down
VESA MOUNTING	100 x 100 mm
COLOUR	Black

4. ACCESSORIES


DRIVER	multi-touch: Windows7/8 (HID compliant), single-touch: Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX)
INCLUDED ACCESSORIES	AC adapter, power cable, DVI signal cable, VGA (D-Sub) signal cable, USB cable, Touch Panel Driver Disk (CD-ROM), quick start guide, safety guide
OPTIONAL ACCESSORIES	remote control OSD key

5. POWER MANAGEMENT

POWER SUPPLY	DC 12V
POWER SUPPLY UNIT	external
POWER USAGE	14 W typical; max. 2 W in Power management mode
POWER MANAGEMENT	VESA DPMS

6. DIMENSIONS & WEIGHT

DIMENSIONS W X H X D	381 x 285.5 x 202 mm
WEIGHT	4.3 kg



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION (). ALL RIGHTS RESERVED.