


990XA-GD55 (MS-7640v4.0) ATX Mainboard

Supports AMD® PhenomII™ X8/ X6/ X4/ X3/ X2, Athlon™ IIX 4/ X3/ X2 and Sempron processors in the AM3 package



Mainboard Specification

<p>Processor Support</p> <ul style="list-style-type: none"> Supports AMD® PhenomII™ X8/ X6/ X4/ X3/ X2, Athlon™ IIX 4/ X3/ X2 and Sempron processors in the AM3+ package <p>Hyper Transport</p> <ul style="list-style-type: none"> Hyper Transport 3.0 up to 5.2 GT/s <p>Chipset</p> <ul style="list-style-type: none"> North Bridge: AMD® RD980 chipset South Bridge: AMD® SB950 chipset <p>Memory Support</p> <ul style="list-style-type: none"> DDR3 2133 (O.C.)/ 1866/ 1600/ 1333/ 1066 DRAM (32GB Max) 4 DDR3 DIMMs/ 2 channels <p>LAN</p> <ul style="list-style-type: none"> Supports LAN PCI-E Gb LAN (10/100/1000) by Realtek® RTL8111E <p>Audio</p> <ul style="list-style-type: none"> HD Audio Realtek® ALC892 Up to 8-channel audio with jack sensing <p>SATA</p> <ul style="list-style-type: none"> 6 SATA 6Gb/s (SATA1~6) ports by AMD SB950 Supports hot plug & asynchronous notification <p>USB 3.0</p> <ul style="list-style-type: none"> 2 USB 3.0 ports (Rear I/O) Power by NEC D720200 	<p>Connectors</p> <ul style="list-style-type: none"> Back panel <ul style="list-style-type: none"> 1 PS/2 keyboard or mouse port 1 Clear CMOS button 1 Coaxial S/PDIF-out port 1 Optical S/PDIF-out port 8 USB 2.0 ports 2 USB 3.0 ports 1 LAN port 6 flexible audio jacks On-Board Connectors <ul style="list-style-type: none"> 2 USB 2.0 connectors 1 serial port connector 1 Chassis Intrusion connector 1 S/PDIF-Out connector 1 Front Panel Audio connector 1 TPM Module connector <p>Slots</p> <ul style="list-style-type: none"> 2 PCI Express 2.0x16 slots 4 PCI Express 2.0 x1 slots 1 PCI slot, Support 3.3V/ 5V PCI bus Interface <p>Form Factor</p> <ul style="list-style-type: none"> ATX (30.48 cmx 24.38 cm) <p>Feature on Focus</p> <ul style="list-style-type: none"> BIOS code unlocked technology USB Charger Advanced USB 3.0 SATA 6Gb/s DrMOS inside Hi-c Cap on PWM Active Phase Switch feature to save power dynamically USB Safeguard M-Flash included CrossFireX™ SLI support <p>Mounting</p> <ul style="list-style-type: none"> 9 mounting holes
--	--

These specification is subject to change without prior notice.