Fujitsu recommends Windows 8 Pro.



Data Sheet Fujitsu ESPRIMO E410 E85+ Desktop PC

Your Immediately Deliverable Office PC

The Fujitsu ESPRIMO E410 small form factor PC delivers high-quality computing for your office applications and projects. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs. With its new design it fits perfect into the modern office. ENERGY STAR® compatibility ensures a low energy bill.

High performance and best price/performance ratio

Cost-effective system for price-conscious customers

■ 3rd generation Intel® Core™ i3, Core™ i5, and Core™ i7 processors

Flexibility

Freedom of choice with tailored systems, perfect fit for specific requirements

■ Flexible logistic concept - optional customizing program

Reliability

High-quality and functional stability

■ Development and production in Europe

Lifecycle

Hardware continuity for long-term projects

■ Managed lifecycle up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

■ Power supply with 85% efficiency







Components

Processor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) *
	Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) *
	Intel® Core™ i5-3330 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.2 GHz, 6 MB, Intel® HD Graphics 2500)
	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Pentium® processor G870 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2120 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2030 (2 Cores / 2 Threads, 3.00 GHz, 3 MB, Intel® HD Graphics)
	Intel® Pentium® processor G2020 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
	Intel® Celeron® processor G1610 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics)
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other
	variables)
Operating systems	
Operating system	Windows 8 Pro
	Windows 8
	Windows® 7 Professional 64-bit
	Windows® 7 Professional 32-bit
Operating system compatible	openSUSE Linux
	Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via
	http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM
•	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM
	8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM
Hard disk drives (internal)	SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch, SED
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
	HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
	<u> </u>
	HDD SATA II, 5400 rpm, 320 GB, 2.5-inch
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery
	SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk)
	SED (Self-Encrypting Drive)
	<u> </u>
Graphics	NVIDIA® GeForce® GT630 DisplayPort 2GB LP, 2 GB
	DP to DVI-D (single link) Adapter Cable
Drives (optional)	BD Triple Writer SATA slim (tray)
	DVD-ROM
	DVD Super Multi
	MultiCard Reader 24in1 USB 2.0 3.5"
nterface add on cards/components (optional)	
	WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only)
	USB 3.0 PCIe x1
	Gigabit Ethernet PCle x1, DS
	Dual serial card PCIe x1
	שטט אבווטו לטוט ד כול אד

Page 2 / 8 www.fujitsu.com/fts/ESPRIMO

Base unit	ESPRIMO E410 E85+
Mainboard	
Mainboard type	D3120
Formfactor	μATX
Chipset	Intel® H61
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	16 GB
Memory frequency	1600 MHz
Memory notes	Dual channel support.
•	For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1000 MBit/s Realtek RTL 8111E
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software
	Recovery BIOS
	Unified Extensible Firmware Interface (UEFI)
Audio codec	Realtek ALC663
Audio features	High Definition Audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	3
Controller functions	Serial ATA II (3 Gbit)
	NCQ
	AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	 1
Audio: line-out	1
Front audio: microphone	
Front audio: headphone	
USB 2.0 total	8
USB 3.0 total	optional
USB front	2
USB rear	4
USB internal	2
VGA	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	1/1
Ethernet (RJ-45)	1
Input device / components	
	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse
	KBPC PX ECO
	Mouse M440 ECO
Drive bays	
Drive bays total	3
3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	3,5 bay can be used for 2,5 drives; optional external bay as internal 3,5";
Slots	
PCI-Express 2.0 x16	1 x (210 mm / 7.87 inch) Low profile
PCI-Express x1	2 x (210 mm / 8.27 inch) Low profile
Graphics on board	
Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
<u>r</u>	

Page 3 / 8

Graphics on board	
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1600 x 1200 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel
(2.3)	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
Graphics features	Dual display support
arapines reacutes	
	DirectX® 10.1 or DirectX® 11 (depending on CPU)
	HDCP support
	Open GL® 3.3 (depending on CPU)
	Open CL® 1.1 (depending on CPU)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85%
Tower emelency note	0-Watt mode with hard-off switch
Dated voltage range	100 V - 240 V
Rated voltage range Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No No
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=262534df-946f-4530-9948-f2f3fbe3764f
Heat dissipation	
•	See white paper Feeren Cookympties
Heat dissipation notes	See white paper Energy Consumption
Noise emission	
Related Processors for noise	Intel® Core™ i7 3770
Standard noise emission	2x2 GB, HDD, ODD, Windows
	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
one in the second cost in production	Bystander position
Standard noise operation mode: CPU	3.4 B / 20 dB(A) Bystander; 22 dB(A) Operator position
50% load	5 5 . 25 55 p. g. opsidion, 22 65 p. g. operation position
Standard noise operation mode: HDD	3.5 B / 22 dB(A) Bystander; 25 dB(A) Operator position
load	3.3 or 22 do(r) dystaliaci, 23 do(r) opeiatol position
Standard noise operation mode: Idle	3.4 B / 20 dB(A) Bystander; 22 dB(A) Operator position
mode	טי בט שטנהן שיאנפוושבו, בב שטנהן טףבופנטו איטונוטוו
	/ E. D. / 20 dD/A\ Dystandor: 26 dD/A\ Operator position
Standard noise operation mode: ODD	4.5 B / 30 dB(A) Bystander; 36 dB(A) Operator position
load Standard poiss operation modes Office	2 / P / 20 dP/A\ Pystandar: 22 dP/A\ Operator position
Standard noise operation mode: Office	3.4 B / 20 dB(A) Bystander; 22 dB(A) Operator position
applications 2.0	

Page 4 / 8 www.fujitsu.com/fts/ESPRIMO

Dimensions / Weight / Environmental	
	330 x 405 x 104 mm
Dimensions (W x D x H)	13.0 x 15.95 x 4.1 inch
0	
Operating position	horizontal / vertical (optional, feet needed)
Weight (lbs)	9 kg 20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Compliance	
Product	ESPRIMO E410
Model	DTL2
Germany	TÜV GS
Europe	CE
Global	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	ENERGY STAR® 5.0
	EPEAT® Gold (dedicated regions)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Additional Software	
	A J. L. a D J. a
Additional software (preinstalled)	Adobe® Reader®
	McAfee Multi Access (anti virus and internet security software; 60 days trial version)
	Win7: Fujitsu Recovery (Hard Disk Based Recovery)
	Win8: Microsoft Push Button Recovery (Hard Disk Based Recovery)
	Microsoft Office - buy license to activate the pre-installed Microsoft Office
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD (BD/DVD playback software for Blu-ray Disc™)
	CyberLink PowerDVD (DVD playback software)
	Nero Essentials XL
Miscellaneous	
Compatibility (references)	
	DMI 2.0
	PC 2001
	WMI 1.5
	USB 2.0
	SMBIOS
Manageability	
Manageability technology	Dock Indata Drivar managament
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code
	Wake up from S5 (off mode) WoL (Wake on LAN)
	WOL (Wake OII LAIN)
Security	
Physical Security	Kensington Lock support
	Eye for padlock
System and BIOS Security	Boot sector virus protection
	Control of external interfaces
User Security	User and supervisor BIOS password
	Hard disk password
	Access protection via external SmartCard reader (optional)
	Access protection via internal SmartCard reader (optional)
Packaging information	
Packaging dimension (mm)	500 x 290 x 540 mm
Packaging dimension (inch)	19.69 x 11.42 x 21.26 inch
r ackaging annension (men)	15.05 A 11.12 A 21.20 High

Page 5 / 8 www.fujitsu.com/fts/ESPRIMO

Packaging information	
Max. quantity / pallet	28
Material - Weight (g) Carton	1140 g
Material - Weight (lbs) Carton	2.51 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	1 year
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local
	regulations, minimum: 1 year material warranty)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Maintenance and Support Services - t	he perfect extension
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	3 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display E19-6 LED



The E19-6 LED combines comfortable ergonomics with best-in-class energy Order Code: saving technology like ECO operation mode.

BDL:TOP-E19-6-LED

Display E22W-6 LED



The E22W-6 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.

Order Code: BDL:TOP-E22W-6-LED

Display E19-6 LED



The Fujitsu Display E19-6 LED combines comfortable ergonomics with best- Order Code: in-class energy saving technology like ECO operation mode.

S26361-K1376-V160

Display E22W-6 LED



The Fujitsu Display E22W-6 LED combines comfortable ergonomics with best-in-class energy saving technology like ECO operation mode.

Order Code: S26361-K1377-V160

Order Code:

BDL:TOP-MOUSE-E-BL

Mouse M440 ECO



Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code: S26381-K450-L200

CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a standard USB-interface for easy Plug & Play use with a notebook or PC. It is S26341-F103-L118 also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

Order Code:

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code: S26391-F7128-L600

WebCam 130 HD2



With the most advanced HD (High Definition / 720p) recording feature and widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you want.

Order Code: S26391-F7136-L5

HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code: S26391-F7139-L5

Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC country specific variation) free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**:

Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4** (**: Country specific variation)

Page 7 / 8 www.fujitsu.com/fts/ESPRIMO

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO E410 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO E410 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-06-27 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions