

SV 271 LITE

Noise Monitoring Station



SV 271 LITE Noise Monitoring Station

SV 271 LITE is a portable monitoring system housed in a waterproof case dedicated for periodic **OUTDOOR** measurements. The low power consumption enables continuous **OPERATION UP TO 3 WEEKS**. The operation time can be even tripled with the external battery (SB272).

The station offers **AUDIO EVENTS** recording and frequency analysis in **1/1 or 1/3 OCTAVES** for noise sources recognition.

The station is based on the **SVAN 971** which can be easily removed from the case and used as a hand-held sound level meter.

SVAN 971 is a Class 1 **TYPE APPROVED** sound level meter in accordance with the IEC 61672-1 standard.

The **TIME-HISTORY** of results such as Leq, Max, Min and Peak with two simultaneous logging steps is saved on a 8 GB microSD card (upgradeable up to 128 GB).

The **EASE OF USE** and fast configuration are ones of the biggest advantages of SV271.

The light-weight microphone protection kit gives an easy access for calibration with an acoustic calibrator. Once the calibration signal is detected, the system starts the **CALIBRATION AUTOMATICALLY**.

The **LARGE WINDSCREEN** is highly efficient in the reduction of a wind noise effects even at high wind speeds.

Military standard **CONNECTORS** provide reliable, robust and waterproof cable connections.

Station uses a **WATERPROOF DC POWER SUPPLY** that is designed for outdoor use.

Station can be powered from the internal battery or external DC power supply and is ready for direct connection of a **SOLAR PANEL**. The powering is managed by the intelligent charging unit.



About SV 271 LITE

SV 271 LITE is an outdoor monitoring system based on the type-approved SVAN 971 Class 1 sound level meter that can be easily removed from the case and used as hand-held sound level meter.

The IP 65-rated case contains a lead-acid battery which operating life of 21 days can be easily extended by connecting an external battery or a solar panel. The intelligent charging unit enables use of a solar panel without expensive controllers or heavy batteries.

The case is fitted with very robust, waterproof connectors (military standard) and is supplied with an IP 65 external power supply.

The light-weight microphone protection kit can be easily installed on a mast with standard mounting threads.

All accessories fit conveniently into a second carrying case. The system provides broad-band results such as Leq, Max, Min and Peak with all standard weighting filters together with an incredible time-history logging feature with two adjustable logging steps.

For noise sources recognition the SV 271 LITE offers options for Audio Events recording and frequency analysis in 1/1 or 1/3 octave bands.



What's inside the SV271 LITE?

The SV 271 LITE kit consists of two carrying cases. The main unit is a waterproof carrying case with internal 17 Ah battery and internal charging unit supporting powering from external DC or solar panel. The SVAN 971 Class 1 sound level meter is installed inside. The outdoor power supply and outdoor microphone kit are packed inside the second transportation case. The kit includes license for SvanPC++ software and has its factory calibration certificate and 36 months warranty card.




PC Software

SvanPC++ is a PC software providing functions such as measurement data downloading from instruments to PC, measurement setups creation basic Leq/RMS recalculation, measurement results in text, table and graphical form of presentation, export data to spread sheet or text editor applications.

Optional functions



The option for **1/1 or 1/3 OCTAVE REAL-TIME ANALYSIS** allows the analysis of the noise frequency contents. It can be activated at any time by ordering an activation code.




The option of **AUDIO EVENT RECORDING** works during measurement and is logged in parallel to time history. Once downloaded to PC it can be played back. Settings such as triggers or recording time are adjustable. It can be activated at any time by ordering an activation code.



SvanPC++ ENVIRONMENTAL MEASUREMENTS module is designed for post-processing of data recorded by monitoring station. The module offers a powerful calculator and an automated noise event finder for noise source identification. SvanPC++_EM allows to combine and compare data from multiple measurements as well as create and save reports in MS Word™ templates. The module can be activated at any time by ordering the activation code or hardware key.

Optional accessories to SV271 LITE




SV36
Class 1 Acoustic
Calibrator
94 dB / 114 dB at
1 kHz



SB271
Solar Panel
to Monitoring
Station



SB272
External 33 Ah
Battery
to Monitoring
Station



SA206
Mast for
Microphone
Protection Kit



SV 271 Technical Specifications

Standards	Class 1: IEC 61672-1:2013; Class 1: IEC 61260-1:2014
Weighting Filters	A, B, C, Z
Time Constants	Slow, Fast, Impulse
RMS Detector	Digital True RMS detector with Peak detection, resolution 0.1 dB
Microphone Protection Kit	SA271 outdoor protection kit (IP 65) with an extension cable
Microphone	ACO SV 7052E, 35 mV/Pa, prepolarised 1/2" condenser microphone
Preamplifier	SV 18 detachable
Linear Operating Range	25 dBA RMS ÷ 140 dBA Peak (in accordance to IEC 61672)
Dynamic Measurement Range	15 dBA RMS ÷ 140 dBA Peak (typical from noise floor to the maximum level)
Internal Noise Level	less than 15 dBA RMS
Dynamic Range	>110 dB
Frequency Range	10 Hz ÷ 20 kHz
Meter Mode Results	Elapsed time, Lxy (SPL), Lx _{eq} (LEQ), Lx _{peak} (PEAK), Lx _{ymax} (MAX), Lx _{ymin} (MIN), LR (ROLLING LEQ OPTION), Ovl (OVERLOAD), Lx _{ye} (SEL), LN (LEQ STATISTICS), Lden, LEPd, Ltm3, Ltm5
Statistics	Simultaneous measurement in three profiles with independent set of filters (x) and Detectors (y)
Audio Recording ¹ (optional)	L _n (L ₁ -L ₉₉), complete histogram in meter mode
1/1 Octave Analysis ¹ (optional)	Audio events recording, trigger and continuous mode, 12 kHz sampling rate, wav format
1/3 Octave Analysis ¹ (optional)	Real-time analysis meeting Class 1 requirements of IEC 61260, center frequencies from 31.5 Hz to 16 kHz
Data Logger	Real-time analysis meeting Class 1 requirements of IEC 61260, center frequencies from 20 Hz to 20 kHz
Memory	Time-history logging of summary results, spectra with adjustable double logging steps down to 100 ms
Power Supply	MicroSD card 8 GB (removable & upgradeable up to 128 GB)
Operating Time on Battery	Waterproof DC power supply 15 V , 60 W (acceptable voltage range 11 V ÷ 30 V)
Environmental Conditions	Built-in battery 17 Ah / 12 V
Dimensions	Secondary external battery 33 Ah / 12 V (optional)
Weight	Solar panel (optional)
	Up to 21 days ²
	Test conditions: meter mode, display dimmed, 100 ms time-history logger, continuous event recording
	Temperature -10 °C ÷ +50 °C
	305 x 270 x 194 mm (without cables)
	Approximately 9 kg including battery (without accessories)

¹function parallel to the meter mode

²depending on configuration and environmental conditions

The policy of our company is to continually innovate and develop our products. Therefore, we reserve the right to change the specifications without prior notice.

Proudly distributed by: