



119.95 EUR incl. 19% VAT, plus shipping

- Intel WiFi, Intel WiDi !
- Dual Gigabit LAN !
- Gigabyte Features !
- Intel Ivy/Sandy Bridge !

Features :

- Intel Z77
- RAM: 2x DDR3
- Expansion: 1x PCIe 3.0 x16
- External: 1x DVI-I, 2x HDMI, 2x USB 3.0, 4x USB 2.0, 2x Gb LAN (Realtek), 7.1 Audio (ALC892), 1x PS/2 Combo
- Internal: 2x USB 3.0, 2x USB 2.0, 2x SATA 6Gb/s, 2x SATA II, 1x CPU-Lüfter PWM, 1x Lüfter PWM, 1x serial
- Notes: Mini-ITX, UEFI, All Solid Capacitors, WLAN 802.11b/g/n, Bluetooth 4.0

	 Support for Intel[®] Core[™] i7 processors/Intel[®] Core[™] i5 processors/Intel[®] Core[™] i3 processors/Intel[®] Pentium[®] processors/Intel[®] Celeron[®] processors in the LGA1155 package
CPU	2. L3 cache varies with CPU
	(Some Intel [®] Core [™] processors require a graphic card, please refer "CPU support List" for more information.)
Chipset	1. Intel [®] Z77 Express Chipset
Memory	 2 x 1.5V DDR3 DIMM sockets supporting up to 16 GB of system memory * Due to a Windows 32-bit operating system limitation, when more than 4 GB of physical memory is installed, the actual memory size displayed will be less than the size of the physical memory installed.
	2. Dual channel memory architecture
	3. Support for DDR3 1600/1333/1066/800 MHz memory modules
	4. Support for non-ECC memory modules
	5. Support for Extreme Memory Profile (XMP) memory modules
	(Please refer "Memory Support List" for more information.)



Onboard Graphics	Integrated Graphics Processor:
	1. 1 x DVI-I port, supporting a maximum resolution of 1920x1200
	2. 2 x HDMI ports, supporting a maximum resolution of 1920x1200
Audio	1. Realtek ALC892 codec
	2. High Definition Audio
	3. 2/4/5.1/7.1-channel
	4. Support for S/PDIF Out
LAN	1. 2 x Realtek GbE LAN chip (10/100/1000 Mbit)
Wireless Communication	1. Wi-Fi 802.11 b/g/n, Supports Intel Wireless Display (WiDi)
module	2. Bluetooth 4.0, 3.0+HS, 2.1+EDR
Expansion Slots	 1 x PCI Express x16 slot, running at x16 (The PCIEX16 slot conforms to PCI Express 3.0 standard.) * Whether PCI Express 3.0 is supported depends on CPU and graphics card compatibility.
Storage Interface	Chipset:
	1. 2 x SATA 6Gb/s connectors (SATA3 0/1) supporting up to 2 SATA 6Gb/s devices
	2. 2 x SATA 3Gb/s connectors (SATA2 2/3) supporting up to 2 SATA 3Gb/s devices
	 Support for RAID 0, RAID 1, RAID 5, and RAID 10 * When a RAID set is built across the SATA 6Gb/s and SATA 3Gb/s channels, the system performance of the RAID set may vary depending on the devices being connected.
USB	Chipset:
	1. Up to 4 USB 3.0/2.0 ports (2 ports on the back panel, 2 ports available through the internal USB header)
	2. Up to 6 USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header)



- 1. 1 x 24-pin ATX main power connector
- 2. 1 x 4-pin ATX 12V power connector
- 3. 1 x serial port header
- 4. 2 x SATA 6Gb/s connectors
- 5. 2 x SATA 3Gb/s connectors
- 6. 1 x USB 3.0/2.0 header

7. 2 x USB 2.0/1.1 headers

- Internal I/O Connectors
- 8. 1 x CPU fan header

 - 9. 1 x system fan header
 - 10. 1 x front panel header
 - 11. 1 x front panel audio header
 - 12. 1 x S/PDIF Out header
 - 13. 1 x Clear CMOS jumper
 - 1. 1 x PS/2 keyboard/mouse port
 - 2. 2 x HDMI ports
 - 3. 2 x antenna connectors
 - 4. 1 x DVI-I port
- Back Panel Connectors
 - 5. 2 x USB 3.0/2.0 ports
 - 6. 4 x USB 2.0/1.1 ports
 - 7. 2 x RJ-45 ports
 - 8. 1 x optical S/PDIF Out connector
 - 9. 5 x audio jacks (Center/Subwoofer Speaker Out, Rear Speaker Out, Line In, Line Out, Mic In)

I/O Controller 1. iTE I/O Controller Chip



- 1. System voltage detection
- 2. CPU/System temperature detection
- H/W Monitoring
- 3. CPU/System fan speed detection
 - 4. CPU fan speed control
 * Whether the CPU fan speed control function is supported will depend on the CPU cooler you install.
 - 1. 2 x 64 Mbit flash

BIOS

3. Support for DualBIOS[™]

2. Use of licensed AMI EFI BIOS

- 4. PnP 1.0a, DMI 2.0, SM BIOS 2.6, ACPI 2.0a
- 1. Support for @BIOS
- 2. Support for Q-Flash
- 3. Support for Xpress Install
- Support for EasyTune
 * Available functions in EasyTune may differ by motherboard model.
- 5. Support for eXtreme Hard Drive (X.H.D)

Unique Features

- 6. Support for Auto Green
- 7. Support for ON/OFF Charge
- 8. Support for Q-Share
- 9. Support for EZ Setup
- 10. Support for Intel Wireless Display (Intel WiDi)
- 11. Exclusive Bluetooth 4.0/WiFi module
- 1. Norton Internet Security (OEM version)
- 2. Intel[®] Rapid Start Technology

Bundle Software

- 3. Intel[®] Smart Connect Technology
- 4. Intel[®] Smart Response Technology



Operating System	1. Support for Microsoft [®] Windows 8/7/XP
Form Factor	1. Mini-ITX Form Factor; 17.0cm x 17.0cm
Remark	 Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website.
I CHIAIN	2. Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP SP1/SP2. If drivers are available from the vendors, we will update them on the GIGABYTE website.