

# ASROCK AM3+ N68-VS3 FX M-ATX 2000MT/S



- Product Group: Motherboards
- Manufacturer: ASROCK
- SKU: CS23683
- Product Name: ASRock N68-VS3 FX (Socket AM3+/GeForce 7025/DDR3/S-ATA 300/Micro ATX)
- Web Address: [www.asrock.com](http://www.asrock.com)
- Model Number: N68-VS3 FX
- Package Type: Retail
- BIOS:
  - 8Mb AMI Legal BIOS
  - Supports Plug and Play
  - ACPI 1.1 Compliance Wake Up Events
  - Supports jumperfree
  - SMBIOS 2.3.1 Support
  - CPU
  - VCCM Voltage Multi-adjustment
- Chipset: NVIDIA GeForce 7025/nForce 630a
- CPU Interface: Socket AM3+
- CPU Support: <http://www.asrock.com/mb/cpu.asp?Model=N68-VS3%20FX>
- Front Side Bus: 2000MT/s
- RAM Technology: DDR3 (Dual Channel)
- RAM Slots: 2 x 240-Pin

- RAM Speeds:
  - DDR3 800
  - DDR3 1066
  - DDR3 1333
  - DDR3 1600
- Max. Memory Support: 8GB
- Expansion Slots:
  - 1 x PCI Express x16
  - 1 x PCI
- Storage Controller(s):
  - 1 x P-ATA/133
  - 4 x S-ATA/300
  - RAID 0
  - RAID 1
  - RAID 0+1
  - RAID 5
  - JBOD
- On-Board LAN:
  - Realtek PHY RTL8201EL
  - Speed: 10/100 Ethernet
  - Supports Wake-On-LAN
  - Supports PXE
- On-Board Audio: 5.1 CH HD Audio (VIA VT1705 Audio Codec)
- On-Board Video:
  - Integrated NVIDIA GeForce 7025 graphics
  - DX9.0 VGA, Pixel Shader 3.0
  - Max. shared memory 256MB
  - Supports D-Sub with max. resolution up to 1920x1440 @ 60Hz
- Back Panel I/O Ports:
  - 1 x PS/2 Mouse
  - 1 x PS/2 Keyboard
  - 1 x VGA
  - 4 x USB 2.0
  - 1 x LAN
  - 3 x Audio
- Internal I/O Connectors:
  - 1 x 24-pin ATX Power
  - 1 x 4-pin ATX 12V Power
  - 1 x Print port header
  - 1 x COM header
  - Front panel audio connector
  - 2 x USB 2.0 headers
- Form Factor:
  - Micro ATX
  - 216mm x 178mm

- Net Weight: 425g
- Gross Weight: 0.72Kg
- Special Features:
  - Integrated NVIDIA GeForce 7025 graphics, DX9.0 VGA, Pixel Shader 3.0
  - 5.1 CH HD Audio (VIA VT1705 Audio Codec)
  - Supports ASRock XFast USB, XFast LAN Technologies
  - Supports ASRock Instant Boot, Instant Flash, OC DNA, APP Charger, SmartView
- Package Contents:
  - Motherboard
  - Quick Installation Guide
  - 2 x S-ATA Data Leads
  - Backplate
  - Driver Disk