

Product details CFT-650-14C

With an **extreme silent 14cm fan** and the **environmental conscious 80+ efficiency features**, which fulfil the latest high-end standard. The easy-to-handle "**cable management**" ensures that no unnecessary cables disturb the optimal air circulation within a chassis. This series is not only a Gamer's dream...



 zoom

Highlights:

- PS2 Form factor
- 650 Watt Intel / AMD
- EPS12V for Dual Processor Mainboards
- ATX 2.3 Specification
- **Cable management**
- All cables in 'net tube'
- 140mm **silent** fan 25~39 dB
- 'full range' input
- active PFC (Power Factor Correction)
- AFC (Automatic Fanspeed Control)
- OVP (Over Voltage Protection)
- OCP (Over Current Protection)
- OTP (Over Temperature Protection)
- 2x PCI Express connectors for all powerful graphic cards (SLI / Crossfire)
- **>80% Efficiency**



Technische Daten

Specification:

AC Input:	100V~120V 8A 220V~240V 4A	Voltage:	+5V	+3,3V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB
Frequency:	47-63 Hz	Current:	28A	30A	18A	18A	18A	18A	0.8A	3A
			180W MAX.		624 W MAX.				9,6W	15W
MAX. LOAD:	650W	Combined Load:								



Dimension:

Security:

15,4 cm x 15 cm x 8,5 cm (TxBxH)



Fixed cables:

Connector:		
Description:	20/24 Pin ATX	4 Pin P IV
Q'ty:	1	1

Modular cables:

Connector:						
Description:	6 Pin PCIe	8 Pin PCIe (6+2)	PATA	Floppy	SATA	8 Pin EPS12V (4+4)
Q'ty:	1	1	6	2	4	1

Hi - POT OK

 CHIEFTEC




8-pin +12V Power Connector



6-pin PCI-E Connector



4-pin Peripheral and Floppy Power Connector



S-ATA Connector



07	08	09
10	11	12