



Xerox® 700/700i/770 Digital Colour Press - Europe Paper and Specialty Media Guide - July 2015

For your convenience, this guide contains three lists:

- Recommended Media List
- Custom Media List
- Antalis Media Compatibility Matrix

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.

Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

Learn more at www.performance-guaranteed.com

The Custom Media List contains custom media that have been tested on Xerox® digital printing equipment. Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox® digital printing equipment. Customers should validate the Best Practices for Operation are acceptable for their application. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that expectations are met.

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

Learn more at www.performance-guaranteed.com

General Information:

Media recommendations made in this publication are based on qualification tests conducted using standard test images with moderate to heavy image area coverage. Test machines are maintained within specifications defined by user documentation.

* Testing environment: Temperature 23°C±2, Relative Humidity range 20-50%.

Reliability is based on your operating environment and application mix.

Machine reliability specifications may be affected by high usage of heavy weight and speciality stocks. In addition, variances in machine reliability may occur due to extended use of some media types.

Customers should inquire directly of their paper distributor or manufacturer for any guarantees they may offer. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to ensure their expectations are met.



© 2015 Antalis International. All rights reserved. Xerox® and Xerox Design® are trademarks of Xerox Corporation in the United States and other countries and are used under license from Xerox Corporation. Antalis International is a trademark licensee of Xerox Corporation.

Xerox® 700/700i/770 Digital Colour Press - Recommended Material List - Europe - July 2015

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

		Standard Cut Sizes			Grammage Weight (g/m ²) Weight of the paper in grams per square metre	Xerox® 700/700i/770 Trays/Weight Selection and Best Practices for Operation											
		A4 210x297 mm	A3 297x420 mm	SRA3 120x450 mm		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		
Weight Range Specification																	
Instructions for Printing one side (Simplex) or two sides (Duplex)																	
Business Papers (Monochrome and text printing)																	
	Decurler Setting paper type					60-80 gsm	81-90 gsm	91-105 gsm	106-128 gsm	129-150 gsm	151-176 gsm	177-220 gsm	221-256 gsm	257-300 gsm			
Xerox® Premier 80 gsm	A	003R91720	003R91721		80	OK All Trays	OK All Trays										
Xerox® Premier 90 gsm	A	003R91854	003R91853		90	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Business 90 gsm	A	003R91820	003R91821		80	OK All Trays	OK All Trays										
Xerox® Exclusive 80 gsm	4-hole A	003R91712	003R90209		80	OK All Trays	OK All Trays										
Xerox® Exclusive 90 gsm	A	003R90208	003R90618		90	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Premium Papers (Colour and high area coverage applications)																	
	Decurler Setting paper type																
Xerox® Colour Impressions 80 gsm	A	003R97661	003R97662		80	OK All Trays	OK All Trays										
Xerox® Colotech® Gold 90 gsm	A	003R98837	003R98839	003R98840	90	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colotech® 90 gsm	A	003R94641	003R94642	003R95838	90	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colour Impressions 90 gsm	A	003R97663	003R97664	003R97665	90	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colotech® Gold 100 gsm	A	003R98842	003R98844	003R98845	100	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colotech® 100 gsm	A	003R94646	003R94647	003R95839	100	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colotech Natural White 100 gsm	A	003R97102	003R97103	003R97275	100	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colour Impressions 100 gsm	A	003R97666	003R97667	003R97668	100	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colotech® Gold 120 gsm	B	003R98847	003R98848	003R98849	120	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colotech® 120 gsm	B	003R94651	003R94652	003R95840	120	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Xerox® Colour Impressions 120 gsm	A	003R98685	003R97669	003R97670	120	OK All Trays	OK All Trays	OK All Trays	OK All Trays								
Uncoated Heavy Stocks																	
	Decurler Setting paper type																
Xerox® Colour Impressions 160 gsm	A	003R98007	003R98008	003R98686	160	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Xerox® Colotech® Gold 160 gsm	A	003R98852	003R98854	003R98855	160	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Xerox® Colotech® 160 gsm	A	003R94656	003R94657	003R95841	160	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Xerox® Colotech Natural White 160 gsm	A	003R95956	003R95957	003R97276	160	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Uncoated Heavy Stocks																	
	Decurler Setting paper type																
Xerox® Colotech® Gold 200 gsm	A	003R97967	003R97968	003R97969	200	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Xerox® Colotech® 200 gsm	A	003R94661	003R94662	003R95842	200	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Xerox® Colotech Natural White 200 gsm	A	003R95958	003R95959	003R97277	200	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			
Xerox® Colotech® Gold 220 gsm	A	003R97971	003R97972	003R97973	220	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays	OK All Trays			

Xerox® 700/700i/770 Digital Colour Press - Recommended Material List - Europe - July 2015

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

		Standard Cut Sizes			Grammage	Xerox® 700/700i/770 Trays/Weight Selection and Best Practices for Operation																			
		A4 210x297 mm	A3 297x420 mm	SRA3 320x450 mm	Weight of the paper in grams per square metre	60-80 gsm		81-90 gsm		91-105 gsm		106-128 gsm		129-150 gsm		151-176 gsm		177-220 gsm		221-256 gsm		257-300 gsm			
Instructions for Printing one side (Simplex) or two sides (Duplex)					Weight of the paper in grams per square metre	IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7		IOT: Trays 1, 2, 3, 4 Bypass: Tray 5 OHCF: Trays 6, 7			
Specialties						Simplex	Duplex	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex	Simplex	Duplex		
Compatible with "Standard" mode only if using Xerox® 770	Decurler Setting paper type																								
Xerox® ValuPeelCard Coated 500 Sheet Box	A	Maximum 50 Sheet stacks 003R97953			216															OK All Trays	OK All Trays				
Xerox® ValuPeelCard Uncoated 500 Sheet Box	A	Maximum 50 Sheet stacks 003R97952			216																OK All Trays	OK All Trays			
Xerox® ValuPerfCard Uncoated 500 Sheet Box	A	Maximum 50 Sheet stacks 003R97690			216																OK All Trays	OK All Trays			
Xerox® DocuMagnet Uncoated 500 Sheet Box	A	Maximum 50 sheet stacks. Do not image base sheet in card area. 003R96072			216																OK All Trays				
Xerox® Business Cards, 10-up	A	Select uncoated 177-220 gsm mode in Tray image side up. 003R97512			195																OK All Trays	Manual Duplex			
Xerox® Colotech® Superglass Document Folder	A	Coated 221-256 gsm mode for glossy, Uncoated 221-256 gsm for matt 003R97634			250																	Bypass Tray	Manual Duplex		
Transparencies Compatible with "Standard" mode only if using Xerox® 770	Decurler Setting paper type																								
Xerox® Premium Universal Transparency with Paper Backing	Default	003R98199			100 microns 100 microns																OK All Trays	OK All Trays			
Tab Stock Compatible with "Standard" mode only if using Xerox® 770	Decurler Setting paper type																								
Xerox® Colotech® Tabs White 100 x 5 reverse	A	Feed long edge first, tabs trailing 003R97231			200																Tray 5/MSI Bypass				
Xerox® Colotech® Tabs White 50 x 10 reverse	A	003R97232			200																Tray 5/MSI Bypass				
Label Stock Compatible with "Standard" mode only if using Xerox® 770	Decurler Setting paper type				Label Stock (approximately)																				
Xerox® Colour Laser Printer Labels 1 PER A4	C	003R93872			190																OK All Trays				
6 PER A4		003R93873			190																OK All Trays				
8 PER A4		003R93874			190																	OK All Trays			
14 PER A4		003R93875			190																	OK All Trays			
24 PER A4		003R97524			190																OK All Trays				
Xerox® Gloss Coated Labels 1 PER A4	C	003R97288			190																OK All Trays				
Xerox® Colotech® Matt CD Labels & CD Inserts Combi Box	C&A	003R97515			190 & 120																OK All Trays				
Transfer paper Compatible with "Standard" mode only if using Xerox® 770	Decurler Setting paper type				Weight of Paper																				
Xerox® Universal Transfer Paper		Load transfer paper long edge feed. Coated 151-176 gsm, simplex only, see us output to catch tray or finisher top tray. 003R93544 003R93545			147																Tray 5 only				
Carbonless Paper Compatible with "Standard" mode only if using Xerox® 770	Decurler Setting paper type				Weight of Paper																				
Xerox® Premium Digital Carbonless Paper																									
CB Singles White (W)	A	003R99069			82																OK All Trays	OK All Trays			
CFB Singles White (W)	A	003R99070			86																OK All Trays	OK All Trays			
CFB Singles Yellow (Y)	A	003R99071			86																OK All Trays	OK All Trays			
CF Singles Yellow (Y)	A	003R99076			82																OK All Trays	OK All Trays			
CF Singles Pink (P)	A	003R99077			82																OK All Trays	OK All Trays			
CF Singles White (W)	A	003R99075			82																OK All Trays	OK All Trays			
2 Part Straight / Reverse W/Y	A	003R99105			82 / 82																OK All Trays	OK All Trays			
2 Part Straight / Reverse W/P	A	003R99107			82 / 82																OK All Trays	OK All Trays			
2 Part Straight / Reverse W/Y	A	003R99133			82 / 82																OK All Trays	OK All Trays			
3 Part Reverse P/Y/W	A	003R99109			82 / 86 / 82																OK All Trays	OK All Trays			
3 Part Straight W/Y/P	A	003R99108			82 / 86 / 82																OK All Trays	OK All Trays			
3 Part Straight W/Y/P	A	003R99135			82 / 86 / 82																OK All Trays	OK All Trays			
4 Part Reverse B/P/Y/W	A	003R99112			82 / 86 / 86 / 82																OK All Trays	OK All Trays			
4 Part Straight W/Y/P/B	A	003R99111			82 / 86 / 86 / 82																OK All Trays	OK All Trays			

Xerox® 700/700i/770 Digital Colour Press - Custom Media List - Europe - July 2015

The Custom Media List contains custom media that have been tested on Xerox® digital printing equipment.
 Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox® digital printing equipment.
 Customers should validate the Best Practices for Operation are acceptable for their application. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that expectations are met.

	Size Tested				Xerox® 700/700i/770 Trays/Weight Selection and Best Practices for Operation			
	A4	A3	SRA3	Other	Grammage	Weight Selection (Media Type)	Feed Tray	Best Practices for Operation
Photo Media								
Compatible with "Standard Mode" only if using Xerox® 770								
Xerox® FunFlip				003R96904 216 x 279 mm (8.5"x11")	167	151 - 176 gsm (Coated) Simplex Only	Tray 5 MSI / Bypass	Image quality degradation /deletions may occur if imaged over perforations, die cuts and scores. Maintain un-imaged clearances of 3mm. Single sheet from Tray 5/MSI Bypass. Simplex only application. Registration variability +/- 2.3 mm.
Translucent Paper								
Compatible with "Standard Mode" only if using Xerox® 770								
Xerox® Translucent 105 gsm			007R96577		105	106-128 (Coated) Simplex Only	Any Tray	Acclimatise paper at printer environment for at least 24 hours prior to running. Sheets should be fanned gently before loading into the feed tray. Feed from all trays. Fan sheets well before loading. Simplex only application.
Xerox® Translucent 135 gsm			007R99402		135	151-176 gsm (Coated) Simplex Only	Any Tray	Acclimatise paper at printer environment for at least 24 hours prior to running. Sheets should be fanned gently before loading into the feed tray. Feed from all trays. Fan sheets well before loading. Simplex only application.
Digiboard								
Compatible with "Standard Mode" only if using Xerox® 770								
Xerox® Digiboard Trim & Tape	Variety Pack			003R96921	210	177-220 gsm (Coated) Simplex Only and Face up	Tray 5, Trays 6 & 7 OHCF	Acclimatise paper at printer environment for at least 24 hours prior to running. Sheets should be fanned gently before loading into the feed tray. Feed from Tray 5MSI, single sheet loading only. Trays 6 & 7 OHCF: fan sheets before loading. Simplex only. Face up printing. Avoid printing within 5 mm of perforations and creases.
	CD Wallet			003R96907				
	A4 Folder			003R96908				
	Tent Card			003R96909				
	A5 Folder			003R96910				
	Pillow Pack			003R96911				
	Mug Box			003R96912				
	Wine Sleeve			003R96913				
	Business Card Box			003R96914				
	Tent Card Tall			003R96915				
A4 Show Card			003R96916					
Xerox® Digiboard Perforated & Tabbed	Variety Pack			003R96822	210	177-220 gsm (Coated) Simplex Only and Face up	Tray 5, Trays 6 & 7 OHCF	Acclimatise paper at printer environment for at least 24 hours prior to running. Sheets should be fanned gently before loading into the feed tray. Feed from Tray 5MSI, single sheet loading only. Trays 6 & 7 OHCF: fan sheets before loading. Simplex only. Face up printing. Avoid printing within 5 mm of perforations and creases.
	Tent Card			003R96919				
	Mug Box			003R96922				
	Wine Sleeve			003R96923				
	Tent Card Tall			003R96925				
	CD Wrap			003R96924				
	Door Hanger			003R96926				
	Golf Ball Box			003R96818				
	Desk Tidy			003R96819				
	Card Photo Canvas			003R93331				
Gift Box Lid			003R96820					
Xerox® Digiboard Base Materials	Gift Box Base			003R96821		Not applicable	Not applicable	Base box for 003R96820. Not for printing
	Wine Box Inner			003R96920		Not applicable	Not applicable	Inner box for 003R96913/003R96923. Not for printing

Xerox® 700/700i/770 Digital Colour Press - Custom Media List - Europe - July 2015

The Custom Media List contains custom media that have been tested on Xerox® digital printing equipment.
 Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox® digital printing equipment.
 Customers should validate the Best Practices for Operation are acceptable for their application. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that expectations are met.

	Size Tested				Xerox® 700/700i/770 Trays/Weight Selection and Best Practices for Operation			
	A4	A3	SRA3	Other	Grammage	Weight Selection (Media Type)	Feed Tray	Best Practices for Operation
Premium NeverTear Polyester Compatible with "Standard Mode" only if using Xerox® 770								
Xerox® Premium NeverTear 95µm	003R98056					129-150 (Coated) Simplex / Manual Duplex Only	Tray 5, Trays 6 & 7 OHCF	Select Face-Up Delivery to the Offset Catch Tray. Stacking may be compromised due to static. Not intended for extensive/exclusive usage.
Xerox® Premium NeverTear 120µm	003R98058					151-176 (Coated) Simplex / Manual Duplex Only	Tray 5, Trays 6 & 7 OHCF	Select Face-Up Delivery to the Offset Catch Tray. Stacking may be compromised due to static. Not intended for extensive/exclusive usage.
Xerox® Premium NeverTear 145µm	003R98091					177-220 (Coated) Simplex / Manual Duplex Only	Tray 5, Trays 6 & 7 OHCF	Select Face-Up Delivery to the Offset Catch Tray. Stacking may be compromised due to static. Not intended for extensive/exclusive usage. Image quality may be improved using a Custom Paper setting with Image Transfer set to 150%.
Premium NeverTear Synthetic Labels Compatible with "Standard Mode" only if using Xerox® 770								
Matt White Polyester, Permanent Adhesive	007R92024				221	221-256 gsm (Label) Simplex only	Tray 5 MSI / Bypass	Load tray with sheets short edge feeding first (SEF). Deliver sheets in face-up orientation.
Gloss White Polyester, Permanent Adhesive	007R92031				236	177-200 gsm (Label) Simplex only	Tray 5 MSI / Bypass	Stacking may be compromised due to high static levels in the sheet
Glass Clear Polyester, Permanent Adhesive	007R92038				217	177-200 gsm (Label) Simplex only	Tray 5 MSI / Bypass	Stacking may be compromised due to high static levels in the sheet
Frosted Polyester, Permanent Adhesive	007R92045				195	177-200 gsm (Label) Simplex only	Tray 5 MSI / Bypass	Load tray long edge feeding first (LEF) and deliver in face-up orientation.
Glass Clear Polyester, Low Tack Adhesive	007R92052				209	177-200 gsm (Label) Simplex only	Tray 5 MSI / Bypass	Stacking may be compromised due to high static levels in the sheet
DuraPaper Label Compatible with "Standard Mode" only if using Xerox® 770								
Xerox® DuraPaper Label	003R97344	003R98645	003R98688			221-256 gsm (Label) Simplex only	Tray 5 MSI / Bypass	Select Face-Up Delivery to the Offset Catch Tray. Not intended for extensive/exclusive usage.

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
● : Certified with excellent print results using specific settings for optimized performance
○ : Prior testing is recommended, printing results depend on print job
○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated, Creative	Conqueror	CX22	Diamond White	100	<p>Media Weight Machine Setting: Uncoated 91 – 105gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 100gsm (100gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Top Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated, Creative	Conqueror	Wove	Brilliant White	100	<p>Media Weight Machine Setting: Uncoated 91 – 105gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 100gsm (100gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Uncoated, Creative	Conqueror	Wove	Brilliant White	300	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 50 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Up Only / Duplex = Face Up Face Up / Down Output Orientation: Up Only LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 50	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated, Creative	Conqueror	Laid	Brilliant White	100	<p>Media Weight Machine Setting: Uncoated 91 – 105gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 100gsm (100gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = 1.5mm AI / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (no latitude) for this device. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the away from seam side of the test media despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Uncoated, Creative	Conqueror	Laid	Brilliant White	220	<p>Media Weight Machine Setting: Uncoated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 220gsm (220gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 50 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 50	<p>4 Point Curl - PASSED Simplex = 2.5mm TI / Duplex = 5mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '60' for side 1 & '50' for side 2 are at or near the lowest transfer capability (no latitude) for this device. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the away from seam side of the test media despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. In addition to moderate levels of mottle, the 'lined' texture' / 'structure' of the sheet surface was visible within the image printed.</p>	○
Uncoated, Creative	Conqueror	Iridescent	Silver Mist	120	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Right Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = 2.5mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '60' for side 1 & side 2 are near the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured/rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Although the media is an uncoated type sheet, it ran more reliably in the Coated run mode. Jams may occur when using the 'Uncoated' run mode. The reliability results reflect output using the 'Coated' run mode.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ◦ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated, Creative	Conqueror	Wove	Brilliant White	220	Media Weight Machine Setting: Uncoated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 220gsm (220gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 60	4 Point Curl - PASSED Simplex = 4.5mm TI / Duplex = Flat Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Side Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured/rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Conqueror	Bamboo	Natural White	250	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 250gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = 2mm TI / Duplex = 1.25mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Side Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate to high levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured/rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it in the Feed Tray. Applying the Multi Feed Support Table may assist with improving reliability.	○
Uncoated, Creative	Curious Collection	Matter	Ibizenca Sand	135	Media Weight Machine Setting: Uncoated 129 – 150 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 135gsm (135gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 100 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = Default Side 2 = Default	4 Point Curl - PASSED Simplex = Flat / Duplex = N/A Uncoated Side Image Quality = PASSED Uncoated Side Image Quality = N/A Toner Adhesion = PASSED Seam Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = FAIL w / Moderate to High Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab, of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The 12 jams recorded during simplex testing were all the result of misfeeds. Feed components contaminated with sheet surface coating was the source of the misfeeds.	○
Uncoated, Creative	Curious Collection	Skin	Extra White	270	Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 270gsm (270gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 50 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up Only / Duplex = Face Up Only LEF / SEF: SEF	Side 1 = 50 Side 2 = 50	4 Point Curl - PASSED Simplex = Flat / Duplex = 1.5mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & side 2 are at the lowest transfer capability (no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Uncoated, Creative	Curious Collection	Metallics	Ice Silver	300	Media Weight Machine Setting: Coated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 100 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up Only / Duplex = Face Up Only LEF / SEF: SEF	Side 1 = 80 Side 2 = 100	4 Point Curl - CAUTION Simplex = 9.25mm TI / Duplex = 7mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Uncoated, Creative	Curious Collection	Matter	Desiree Red	270	Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 270gsm (270gsm listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 100 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF	Side 1 = Default Side 2 = Default	4 Point Curl - N/A Simplex White = N/A Duplex White = N/A Uncoated Side 1 Image Quality = FAIL Uncoated Side 2 Image Quality = FAIL Toner Adhesion = PASSED Both Sides Simplex Stacking = N/A Duplex Stacking = N/A Contamination = FAIL w / Moderate to High Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. High levels of mottle were observed in some solid area colours and in halftones of 80% and less on both sides of the test media despite applying a Custom Paper Profile. Mottle levels were likely related to the sheets surface characteristics (rough / textured) and the test devices inability to 'fill' in the sheets surface variations. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. The jams recorded during testing were the result of detected multi sheet feeds and misfeeds.	○

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated, Creative	Curious Collection	Skin	Grey	270	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 270gsm (270gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Curious Collection	Metallics	Cryogen White	240	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 240gsm (240gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Curious Collection	Metallics	Europa Ivory	240	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 240gsm (240gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 50 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & '60' side 2 is near or at the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Curious Collection	Metallics	Super Gold	300	Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 90 Output Destination: Finisher Top Right Output Tray Simplex / Duplex: Simplex & Manual Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF	Side 1 = 90 Side 2 = 90	4 Point Curl - CAUTION Simplex = 8mm TI / Duplex = 2.5mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = CAUTION w / Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Although some types of media at this basis weight were run auto duplex, Manual Duplex is recommended. Duplex Reliability results reflect media run in the Manual Duplex run mode. Minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Although contamination levels did not cause any loss of functionality to the test device, contamination levels will likely increase on longer runs.	●
Uncoated, Creative	Keaycolour	Original	Snow White	300	Media Weight Machine Setting: Coated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up Only / Duplex = Face Up Only LEF / SEF: SEF	Side 1 = 50 Side 2 = 60	4 Point Curl - PASSED Simplex = 5mm TI / Duplex = 2mm T Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & '60' for side 2 are near and / or at the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Keaycolour	Original	Tangerine	120	Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSED Simplex = 2.5mm TI / Duplex = 1.75mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured/rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ◦ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated, Creative	Keaycolour	Original	Guardsman Red	300	Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 90 Output Destination: Finisher Top Right Output Tray Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF	Side 1 = 90 Side 2 = 90	4 Point Curl - CAUTION Simplex = 7.25mm TI / Duplex = 5mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Uncoated, Creative	Pop/Set	Colours	Grey	120	Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 90 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Uncoated, Creative	Pop/Set	Colours	Cosmo Pink	240	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 240gsm (240gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 50 Side 2 = 60	4 Point Curl - PASSED Simplex = 3.5mm AI / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & '60' side 2 are at or near the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Pop/Set	Colours	Grey	240	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 240gsm (240gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 60	4 Point Curl - PASSEDSimplex = Flat / Duplex = 3.75mm TI/uncoated Side Image Quality = PASSED Uncoated Side Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Creative	Rives	Dot	Bright White	250	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 250gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 100 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: SEF LEF / SEF: SEF	Side 1 = Default Side 2 = Default	4 Point Curl - N/A Simplex = N/A / Duplex = N/A Uncoated Side 1 Image Quality = FAILED Uncoated Side 2 Image Quality = FAILED Toner Adhesion = PASSED Seam Side Simplex Stacking = N/A Duplex Stacking = N/A Contamination = N/A	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate to High levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. High mottle levels were likely the result of the sheets surface properties (textured) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	○
Uncoated, Creative	Rives	Tradition	Pale Grey	250	Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) - Seam Side Down Actual Media Basis Weight: 250gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 70	4 Point Curl - PASSED Simplex = 6mm AI / Duplex = 3mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '60' for side 1 is near the lowest transfer capability (limited latitude) for this device. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. The 3 jams recorded were the result of misfeeds. Minor levels of contamination may have contributed to the cause of misfeeds. Once the feed rolls were cleaned (Feed Rolls were cleaned prior to the Start of the test), testing continued to completion with no more misfeed type jams.	○

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
● : Certified with excellent print results using specific settings for optimized performance
○ : Prior testing is recommended, printing results depend on print job
○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated, Creative	Rives	Design	Bright White	250	<p>Media Weight Machine Setting: Uncoated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 250gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = 1.75mm AI / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured/rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated, Creative	Rives	Matt	Tradition Bright White	270 Long Grain	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 270gsm (270gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF</p>	Side 1 = 90 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = 3mm TI / Duplex = 2.5mm TI Uncoated Side 1 Image Quality = FAIL Uncoated Side 2 Image Quality = FAIL Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate to high levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Moderate mottle levels were likely the result of the sheets surface properties (textured/rough) and the devices inability to 'fill' in the variations of the sheets surface. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it the Feed Tray. Applying the Multi Feed Handling Table may assist with improving reliability.</p>	○
Uncoated, Creative	Rives Sensation	Mat Tradition	Bright White	270 Short Grain	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 270gsm (270gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up Only / Duplex = Only LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & '60' for side 2 are at and / or near the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Graphical Boards	Carta Integra	2 Silk	White	170	<p>Media Weight Machine Setting: Coated 151 – 176 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 167gsm (170gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = 1.5mm TI / Duplex = 1.75mm TI Coated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Graphical Boards	Carta Integra	2 Silk	White	265	<p>Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 260 gsm (265gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Top Tray Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Right Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 90	<p>4 Point Curl - CAUTION Simplex = 1.5mm TI / Duplex = 8mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Despite applying various Decurler settings, the best achievable Duplex Curl measured 8mm, which is the near the upper curl limits expected for this device. Excessive curl would likely lead to pre-mature 'Output Tray Full' messages, a loss in productivity and possible reliability issues on longer runs. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Graphical Boards	Carta Solida	1 Silk	White	185	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 183 gsm (185gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 100 Output Destination: Finisher Top Tray ONLY Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Right Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 100	<p>4 Point Curl - PASSED Simplex = 2mm AI / Duplex = 3.75mm TI Coated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = CAUTION Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Excessive Sheet Scatter was observed when delivering the duplex imaged output to the Finisher Stacker Tray. Finisher Top Tray is the recommended output tray when auto duplexing this media. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Graphical Boards	Carta Solida	1 Silk	White	260	Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 260 gsm (257gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 100 Output Destination: Finisher Top Tray Simplex / Duplex: Simplex & Manual Duplex Simplex Decurler Settings: Tray Curl Properties = Setting 'B' / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Setting 'A' / IOT Setting = Middle / Finisher Setting = Left Button Simplex = Face Up / Duplex = Face Up / Down Output Orientation: Face Up LEF / SEF: SEF	Side 1 = 70 Side 2 = 100	4 Point Curl - PASSED Simplex = 4mm AI / Duplex = 3.5mm TI Coated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Graphical Boards	Invercote Creato	2 Matt	White	200	Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 203 gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = *1 / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 90 Side 2 = 90	4 Point Curl - PASSED Simplex = 1mm TI / Duplex = 3.5mm TI Coated Side 1 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	G
Graphical Boards	Invercote Creato	2 Matt	White	240	Media Weight Machine Setting: Coated 221 – 256 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 243 gsm (240gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Manual Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Middle / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = A / IOT Setting = Middle / Finisher Setting = Auto - See Comments Simplex = Face Down / Face Up / Down Output Orientation: Duplex = Face Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 70	4 Point Curl - PASSED Simplex = 2.25mm AI / Duplex = 1mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Graphical Boards	Invercote Creato	2 Matt	White	300	Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 303 gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Top Tray Simplex / Duplex: Simplex & Manual Duplex Simplex Decurler Settings: Tray Curl Properties = A / IOT Setting = Middle / Finisher Setting: Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = A / IOT Setting = Middle / Finisher Setting: Left Button - See Comments Simplex = Face Down / Face Up / Down Output Orientation: Duplex = Face Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSED Simplex = 2.5mm TI / Duplex = 2.75mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Graphical Boards	Invercote G	1 Matt	White	180	Media Weight Machine Setting: Coated - 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 181 gsm (180gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = *1 / Finisher Setting = Left Button - See Comments Simplex = Face Up / Down Output Orientation: Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 100	4 Point Curl - PASSED Simplex = 1mm TI / Duplex = 1.5mm TI Coated Side Image Quality = PASSED Uncoated Side Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = CAUTION Duplex Stacking = FAIL Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media despite applying a Custom Paper Profile setting. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Although Simplex & Duplex Curl measured within expected limits, Simplex & Duplex Stacking had Major Sheet Scatter issues likely resulting from variable sheet to sheet curl. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	○
Graphical Boards	Invercote G	1 Matt	White	240	Media Weight Machine Setting: Coated - 221 – 256 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 243 gsm (240gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 130 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = *1 / Finisher Setting: Left Button - See Comments Simplex = Face Down / Face Up / Down Output Orientation: / Duplex = Face Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 130	4 Point Curl - PASSED Simplex = 1.25mm AI / Duplex = 1mm AI Coated Side Image Quality = PASSED Uncoated Side Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media despite applying a Custom Paper Profile setting. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Graphical Boards	Invercote G	1 Matt	White	300	<p>Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 304 gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Top Tray Simplex / Duplex: Simplex & Manual Duplex Simplex Decurler Settings: Tray Curl Properties = B / IOT Setting = Middle / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = A / IOT Setting = Middle / Finisher Setting = Left Button - See Comments Simplex = Face Down Face Up / Down Output Orientation: / Duplex = Face Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	<p>4 Point Curl - CAUTION Simplex = 6.25mm AI / Duplex = 8mm AI Coated Side Image Quality = PASSED Uncoated Side Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Simplex & Manual Duplex Curl varied despite applying different Decurler settings. Excessive curl would likely lead to pre-mature 'Output Tray Full' messages, a loss in productivity and possible reliability issues on longer runs. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media despite applying a Custom Paper Profile setting. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Graphical Boards	Trucard	1 Gloss	White	200	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Simplex = Face Down Face Up / Down Output Orientation: SEF LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = 2.5mm AI / Duplex = N/A Coated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = N/A Toner Adhesion = PASSED Coated Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight to Minor Levels</p>	<p>It is recommended that the media be fanned vigorously prior to placing it in the Feed Tray. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Graphical Boards	Trucard	1 Gloss	White	240	<p>Media Weight Machine Setting: Coated 221 – 256 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 240gsm (240gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 100	<p>Coated Side Up 4 Point Curl - CAUTION Simplex = 6mm AI / Duplex = 14mm TI Coated Side Down 4 Point Curl - PASSED Simplex = N/A / Duplex = Flat Coated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>It is recommended that the media be fanned vigorously prior to placing it in the Feed Tray. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. When imaged on the uncoated side 1st, duplex curl response improved measuring 'Flat'. Excessive curl would likely lead to pre-mature 'Output Tray Full' messages, a loss in productivity and possible reliability issues on longer runs. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Graphical Boards	Trucard	1 Gloss	White	300	<p>Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Right Button - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Simplex = Face Up Only LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = N/A	<p>4 Point Curl - PASSED Simplex = 6mm TI / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED Coated Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	G
Graphical Boards	Trucard	2 Gloss	White	200	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 194gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Top Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Graphical Boards	Trucard	2 Gloss	White	240	<p>Media Weight Machine Setting: Coated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 240gsm (240gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Simplex & Auto Duplex Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Face Up / Down Output Orientation: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down LEF / SEF: Face Down SEF</p>	Side 1 = 80 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = 2.5mm AI / Duplex = 3mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Graphical Boards	Trucard	2 Gloss	White	300	<p>Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 60 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Up Only / Duplex = Face Up / Down Output Orientation: Up Only LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = 4mm TI / Duplex = 3mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '60' for side 2 is at the lowest transfer capability (no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Graphical Boards	Trucard	1 Matt	White	300	<p>Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 301gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = N/A Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Right Button - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Simplex = Face Up Only / Duplex = Face Up / Down Output Orientation: Only LEF / SEF: SEF</p>	Side 1 = 90 Side 2 = N/A	<p>4 Point Curl - PASSED Simplex = 5mm TI / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED Side 1 Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	G
Graphical Boards	Trucard	2 Matt	White	300	<p>Media Weight Machine Setting: Coated 257 – 300 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Top Tray Only Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Up Only / Duplex = Face Up / Down Output Orientation: Up Only LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	<p>4 Point Curl - CAUTION Simplex = 12mm TI / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Despite applying various Decurler settings, the best achievable Simplex Curl measured 12mm, which is at the upper curl limits expected for this device. Excessive curl would likely lead to pre-mature 'Output Tray Full' messages, a loss in productivity and possible reliability issues on longer runs. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Chromomat	Matt	White	115	<p>Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Chromomat	Matt	White	200	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Claro Gloss	Gloss	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = 3mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
● : Certified with excellent print results using specific settings for optimized performance
○ : Prior testing is recommended, printing results depend on print job
o : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated	Claro Gloss	Gloss	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = Default	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Claro Silk	Silk	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = CAUTION Coated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Image Defects, in the form of 'ripples' / 'waviness', were observed on some of the imaged output. 'Ripples' / 'waviness' may lead to deletions. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	○
Coated	Claro Silk	Silk	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = Default	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	G
Coated	Galerie Art Gloss	Gloss	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = CAUTION Coated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (limited latitude) for this device. Image Defects, in the form of 'ripples' / 'waviness', were observed on some of the imaged output. 'Ripples' / 'waviness' may lead to deletions. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	○
Coated	Galerie Art Gloss	Gloss	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 110 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 90 Side 2 = 110	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	G
Coated	Galerie Art Matt	Matt	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	G

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated	Galerie Art Matt	Matt	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 90	4 Point Curl - PASSED Simplex = 2mm AI / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Coated	Galerie Art Silk	Silk	White	115	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Coated	Galerie Art Silk	Silk	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Coated	Magno Matt	Matt	White	115	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Magno Matt	Matt	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 110 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 110	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Magno Silk	Silk	White	115	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = 2.5mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated	Magno Silk	Silk	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 90	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Coated	Magno Star	Gloss	White	115	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 90	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Magno Star	Gloss	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 110 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = Default	4 Point Curl - PASSED Simplex = 3mm AI / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Maine 1 Face Gloss	1 Gloss	White	110	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 110gsm (110gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = 2mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Maine 1 Face Gloss	1 Gloss	White	150	Media Weight Machine Setting: Coated 129 – 150gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 150gsm (150gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 50 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 50 Side 2 = 50	4 Point Curl - PASSED Simplex = Flat / Duplex = 2mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '50' for side 1 & side 2 is at the lowest transfer capability (no latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Maine Gloss	Gloss	White	115	Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 113gsm (113gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated	Maine Gloss	Gloss	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Novatech Digital Gloss	Gloss	White	115	Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Novatech Digital Gloss	Gloss	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Novatech Digital Silk	Silk	White	115	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = 2mm TI / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Novatech Digital Silk	Silk	White	200	Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Novatech Gloss	Gloss	White	115	Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 7 Actual Media Basis Weight: 115 gsm (115 gsm listed on box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: AutoFace Down Face Up / Down Output Orientation: LEF / SEF: SEF	Side 1 = 50 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & '60' for side 2 are at or near the lowest transfer capability (limited to no latitude) for this device Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated	Novatech Gloss	Gloss	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = 2.25mm AI / Duplex = 2.75mm AI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (limited to no latitude) for this device Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Novatech Silk	Silk	White	115	<p>Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm listed on box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Auto Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = CAUTION Coated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the at Image Defects, in the form of deletions, 'wrinkles' and / or 'ripples/waves', were observed on some of the imaged output. 'Wrinkles', and / or 'ripples/waves' and the resulting deletions were likely related, in part, to the sheets properties and its interaction with Fuser Subsystem components. Traditional Fuser 'Nip' adjustments are not available for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	○
Coated	Novatech Silk	Silk	White	200	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200 gsm listed on box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = "1" / Finisher Setting: Auto Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = 0.5mm TI / Duplex = 1.75mm AI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the at Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	G
Coated	Satimat	Silk	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = 2mm TI / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Satimat	Silk	White	200	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto Simplex = Face Down / Duplex = Face Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated	Tom&Otto Gloss	Gloss	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated	Tom&Otto Gloss	Gloss	White	200	Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Down / Duplex = Face Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Tom&Otto Silk	Silk	White	115	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated	Tom&Otto Silk	Silk	White	200	Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 90	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated, Recycled	Cocoon Gloss	Gloss	White	115	Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 121gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = 1.5mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Coated, Recycled	Cocoon Gloss	Gloss	White	200	Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 192gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 80 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = 1mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Coated, Recycled	Cocoon Silk	Silk	White	115	Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 123gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Down Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 90	4 Point Curl - PASSED Simplex = Flat / Duplex = 1.75mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to Minor Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated, Recycled	Cocoon Silk	Silk	White	200	<p>Media Weight Machine Setting: Coated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 192gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = 4.75mm AI / Duplex = 1.5mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Coated, Recycled	Cyclus Print	Matt	White	90	<p>Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 90gsm (90gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side Image Quality = FAILED Coated Side 2 Image Quality = FAILED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>"Coated 106-128gsm" is the lowest "Coated" setting available for this device. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. Image Defects, in the form of 'wrinkles' and / or 'deletions', were observed on the imaged output despite adjusting the Fuser CRU 'Dia' setting. 'Wrinkles', and the resulting deletions, were likely related, in part, to the sheets properties and its interaction with Fuser Subsystem components. In addition, the sheets basis weight (90gsm) is lower than the lowest basis weight specified by the device (Coated = 106gsm). Traditional Fuser 'Nip' adjustments are not available for this device. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	○
Coated, Recycled	Cyclus Print	Matt	White	115	<p>Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 100 Output Destination: Finisher Top Right Output Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = Default	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight to minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated, Recycled	Cyclus Print	Matt	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 190gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 130 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 130	<p>4 Point Curl - PASSED Simplex = 4mm AI / Duplex = 1mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = CAUTION w / Slight to Minor Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. The one jam occurring during simplex testing was the result of a detected multi sheet feed. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination was 'tacky' to the touch and may have played a part in causing the 1 jam recorded during simplex testing.</p>	●
Coated, Recycled	Digigreen Gloss	Gloss	White	115	<p>Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = CAUTION Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Image Defects, in the form of deletions, were observed on some of the imaged output. Deletions were likely the result of 'waviness' present in the sheets surface after passing through the Fuser CRU during the simplex pass. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Coated, Recycled	Digigreen Gloss	Gloss	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Coated, Recycled	Digigreen Silk	Silk	White	115	<p>Media Weight Machine Setting: Coated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	4 Point Curl - PASSED Simplex = 2mm AI / Duplex = 2mm AI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Coated, Recycled	Digigreen Silk	Silk	White	200	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	4 Point Curl - PASSED Simplex = 3mm AI / Duplex = 1mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Edixion Laser	Plain	White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm (Coated 106-128gsm Recommended) Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Coated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSEDSimplex = Flat / Duplex = 2mm TI Uncoated Side Image Quality = PASSED Uncoated Side Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Edixion Laser	Plain	White	80	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (80gsm listed on box)Uncoated Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting: Auto Face Down Face Up / Down Output Orientation: SEF LEF / SEF:</p>	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSEDSimplex = Flat / Duplex = 2mm TI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Edixion Offset	Plain	White	80	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (80gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSED Simplex = 2mm TI / Duplex = 1.25mm TI Uncoated Side 1 Image Quality = CAUTIONUncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the away from seam side of the test media despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Edixion Offset	Plain	White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or at the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (limited latitude) for this device Minor levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying an adjusted Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
● : Certified with excellent print results using specific settings for optimized performance
○ : Prior testing is recommended, printing results depend on print job
○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated	Edixion Offset	Plain	White	300	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray (OCT, Finisher and / or HCS Top Tray Output Delivery Recommended) Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Up / Duplex = Face Up Face Up / Down Output Orientation: ONLY LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 50	<p>4 Point Curl - PASSED Simplex = 2.5mm AI / Duplex = 1.25mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & '50' for side 2 are near and / or at the lowest transfer capabilities (limited to no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated	Image Digicolour	Plain	White	90	<p>Media Weight Machine Setting: Uncoated 81 – 90 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 90gsm (90gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: ONLY LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = 2mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Uncoated	Image Digicolour	Plain	White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = 1mm AI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capabilities (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated	Image Digicolour	Plain	White	200	<p>Media Weight Machine Setting: Uncoated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 194gsm (200gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: ONLY LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = 2.5mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Uncoated	Image Digicolour	Plain	White	250	<p>Media Weight Machine Setting: Uncoated 221 – 256 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 242gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = 2mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '50' for side 1 & '60' for side 2 are near and / or at the lowest transfer capabilities (limited to no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.</p>	●
Uncoated	Image Digicolour	Plain	White	300	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '50' for side 1 & '60' for side 2 are near and / or at the lowest transfer capabilities (limited to no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated	Image Impact Plus	Plain	White	100	<p>Media Weight Machine Setting: Uncoated 91 – 105 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 100gsm (100gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = 2mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Image Impact Plus	Plain	White	160	<p>Media Weight Machine Setting: Uncoated 151 – 176 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 160gsm (160gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = 1.5mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Image Impact Plus	Plain	White	250	<p>Media Weight Machine Setting: Uncoated 221 – 256 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 242gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 50 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 50	4 Point Curl - PASSED Simplex = Flat / Duplex = 2.75mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '50' for side 1 & side 2 is at the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Slight to minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not cause any loss of functionality to the test device.	●
Uncoated	Image Impact Plus	Plain	White	300	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 297gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Up / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	4 Point Curl - PASSED Simplex = 3mm AI / Duplex = 1.5mm T Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (no latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Olin	Smooth	High White	90	<p>Media Weight Machine Setting: Uncoated 81 – 90gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 90gsm (90gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Olin	Smooth	High White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 70	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated	Olin	Smooth	Cream	200	<p>Media Weight Machine Setting: Uncoated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 50 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 50	4 Point Curl - PASSED Simplex = Flat / Duplex = 2mm TI Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '50' for side 1 & side 2 is at the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Olin	Smooth	Cream	250	<p>Media Weight Machine Setting: Uncoated 221 – 256 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 250gsm (250gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 90 Side 2 = 90	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Uncoated	Olin	Smooth	Cream	300	<p>Media Weight Machine Setting: Uncoated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 300gsm (300gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 80 Output Destination: Finisher Top Right Output Tray Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 80	4 Point Curl - PASSED Simplex = 1.5mm AI / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '50' for side 1 is at the lowest transfer capability (no latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Pioneer Preprint	Plain	White	80	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (80gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Up / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Duplex = 1.5mm TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it in the Feed Tray.	●
Uncoated	Pioneer Preprint	Plain	White	110	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 110gsm (110gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '50' for side 1 & '60' for side 2 are near or at the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it in the Feed Tray.	●
Uncoated	Print Speed LaserJet	Plain	White	75	<p>Media Weight Machine Setting: Uncoated 64 – 80 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 75gsm (75gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 2 is near the lowest transfer capability (limited latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated	Print Speed LaserJet	Plain	White	90	<p>Media Weight Machine Setting: Uncoated 81 – 90gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 90gsm (90gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 80	<p>4 Point Curl - PASSED Simplex = 2.5mm TI / Duplex = Flat Uncoated Side 1 Image Quality = CAUTION Uncoated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated	Print Speed LaserJet	Plain	White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated	Print Speed Offset	Plain	White	60	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 60gsm (60gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = Default / Side 2 = Default Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = N/A / Finisher Setting = N/A Simplex = Face Down / Duplex = N/A Face Up / Down Output Orientation: SEF LEF / SEF: SEF</p>	Side 1 = Default Side 2 = Default	<p>4 Point Curl - PASSED Simplex = 2.5mm AI / Duplex = N/A/Uncoated Side 1 Image Quality = FAIL/Uncoated Side 2 Image Quality = N/A/Toner Adhesion = PASSED One Side Simplex Stacking = FAIL Duplex Stacking = N/A Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Image Defects, in the form of 'wrinkles' and / or 'deletions', were observed on the imaged output despite adjusting the Fuser CRU 'Dial' setting. Because of the severity of the Image Defect, testing was cancelled. 'Wrinkles', and the resulting deletions, were likely related, in part, to the sheets properties and its interaction with Fuser Subsystem components. In addition, the sheets basis weight (60gsm) is lower than the lowest basis weight specified by the device (uncoated = 64gsm). Traditional Fuser 'Nip' adjustments are not available for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	○
Uncoated	Print Speed Offset	Plain	White	80	<p>Media Weight Machine Setting: Uncoated 81 – 90gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (80gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 60 Side 2 = 90	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 is near the lowest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated	Print Speed Offset	Plain	White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 117gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 70 Side 2 = 70	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Uncoated	Scandia 2000	Smooth	White	115	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 115gsm (115gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 100 / Side 2 = 100 Output Destination: Finisher Top Output Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 100 Side 2 = 100	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	G

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated	Scandia 2000	Smooth	Natural	150	Media Weight Machine Setting: Uncoated 129 – 150 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 150gsm (150gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 60 Output Destination: Finisher Top Right Output Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 60	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '60' for side 1 & side 2 is near the lowest transfer capability (limited latitude) for this device. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated	Scandia 2000	Smooth	Ivory	200	Media Weight Machine Setting: Uncoated 177 – 220 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 / Side 2 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 70 Side 2 = 90	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less on the uncoated side of the test media. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Recycled	Cocoon Offset	Plain	White	80	Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 82gsm (80gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 100 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = Default Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	G
Uncoated, Recycled	Cocoon Offset	Plain	White	120	Media Weight Machine Setting: Coated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 120 / Side 2 = 110 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 120 Side 2 = 110	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Although the media is an uncoated type sheet, it ran more reliably in the Coated 106-128gsm run mode. Jams may occur when using the 'Uncoated 106-128gsm' run mode. The reliability results reflect output using the 'Coated 106-128gsm' run mode.	●
Uncoated, Recycled	Cocoon Offset	Plain	White	200	Media Weight Machine Setting: Uncoated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 / Side 2 = 50 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 60 Side 2 = 50	4 Point Curl - PASSED Simplex = 2.5mm TI / Duplex = Flat/Uncoated Side 1 Image Quality = PASSED/Uncoated Side 2 Image Quality = PASSED Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of '60' for side 1 and '50' for side 2 are near and / or at the lowest transfer capability (limited to no latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Uncoated, Recycled	Cocoon Preprint	Plain	White	80	Media Weight Machine Setting: Uncoated 64 – 80 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 82gsm (80gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Simplex & Auto Duplex Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Face Up / Down Output Orientation: SEF LEF / SEF: SEF	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is recommended that the media be fanned vigorously prior to placing it in the Feed Tray.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Uncoated, Recycled	Cocoon Preprint	Plain	White	120	<p>Media Weight Machine Setting: Uncoated 106 – 128gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 120gsm (120gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is recommended that the media be fanned vigorously prior to placing it in the Feed Tray.	●
Uncoated, Recycled	Cocoon Preprint	Plain	White	160	<p>Media Weight Machine Setting: Coated 151 – 176gsm - See Comments Trays: Tray 6 (OHCF) Actual Media Basis Weight: 160gsm (160gsm Listed on Box) Coating: Uncoated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = Default	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Although the media is an uncoated type sheet, it ran more reliably in the Coated 151-176gsm run mode. Jams may occur when using the 'Uncoated 151-176gsm' run mode. The reliability results reflect output using the 'Coated 151-176gsm' run mode.	●
Uncoated, Recycled	Cyclus Offset	Plain	White	70	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 70gsm (70gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	4 Point Curl - PASSED Simplex = 2mm AI / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it in the Feed Tray.	●
Uncoated, Recycled	Cyclus Offset	Plain	White	170	<p>Media Weight Machine Setting: Uncoated 151 – 176 gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 164gsm (170gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 50 / Side 2 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 50 Side 2 = 60	4 Point Curl - PASSED Simplex = 1.5mm TI / Duplex = Flat Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile settings of 'SD' for side 1 and '60' for side 2 are near and / or at the lowest transfer capability (limited to no battude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it in the Feed Tray.	○
Carbonless	Idem Digital	Plain	White	85	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (90gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	Hanging Europe - CAUTION Simplex = 27.5mm CD-AI / Duplex = 20mm CD-Ti Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Minor Levels	Despite applying various Decurler settings, the best Simplex Hanging Curl achieved measured 27.5mm, which is near the upper curl limits expected for this device. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. It is strongly recommended that the media be fanned vigorously prior to placing it in the Feed tray. Although minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components, contamination levels did not reach a point that led to a loss of functionality to the test device or the 2 misfeeds that occurred.	●
Carbonless	Idem Digital	Plain	White	90	<p>Media Weight Machine Setting: Uncoated 81 – 90gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (90gsm Listed on Box) Coating: Uncoated Grain: Long Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = 80	Hanging Europe - CAUTION Simplex = 20mm MD-AI / Duplex = 27.5mm Diag-Ti Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = FAIL w / Moderate Levels	Despite applying various Decurler settings, the best Duplex Hanging Curl achieved measured 27.5mm, which is near the upper curl limits expected for this device. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor to moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	○

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
● : Certified with excellent print results using specific settings for optimized performance
○ : Prior testing is recommended, printing results depend on print job
○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m ²)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Carbonless	Idem Digital	Pre-collated (3-part straight)	White	85	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (Various weights listed on Box) Coating: Uncoated Grain: Long Edge</p> <p>Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex</p> <p>Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Face Down LEF / SEF: LEF</p>	Side 1 = 90 Side 2 = Default	<p>Hanging Euro - CAUTION - See Comments: Simplex White = 40mm MD-AI Simplex Canary = 20mm CD-AI Simplex Pink = Flat Duplex White = 20mm MD-TI Duplex Canary = 20mm CD-TI Duplex Pink = 12.5mm MD-AI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Minor Levels</p>	<p>Each sheet of the 3 Part Carbonless media was measured for simplex & duplex curl. Some of the sheets measured were at or just beyond the upper curl limits expected for this device.</p> <p>Simplex & Duplex curl measurements were achieved when applying the Decurler setting recommended.</p> <p>Decurler settings for a composite set (W/C/P) will vary and are dependent on area coverage, media type, environmental and machine conditions.</p> <p>Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less.</p> <p>Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p> <p>It is strongly recommended that the media be fanned vigorously prior to placing it the Feed Tray.</p> <p>Minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not reach a level that led to a loss of functionality to the test device.</p>	●
Carbonless	Idem Digital	Plain	White	90	<p>Media Weight Machine Setting: Uncoated 64 – 80gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 80gsm (90gsm Listed on Box) Coating: Uncoated Grain: Long Edge</p> <p>Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex</p> <p>Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Up / Down Output Orientation: Down LEF / SEF: SEF</p>	Side 1 = 80 Side 2 = Default	<p>Hanging Europe - CAUTION Simplex = 22.5mm CD-AI / Duplex = 27.5mm CD-TI Uncoated Side 1 Image Quality = PASSED Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Minor Levels</p>	<p>Despite applying various Decurler settings, the best Duplex Hanging Curl achieved measured 27.5mm, which is near the upper curl limits expected for this device. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel.</p> <p>Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p> <p>Minor levels of contamination, in the form of paper dust and / or sheet surface coating were observed on Tray Feed components. Contamination levels did not reach a level that led to a loss of functionality to the test device.</p>	○
Adhesives*	Jetlaser HS	Plain	White	164	<p>Media Weight Machine Setting: Coated 151 – 176gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 164gsm Coating: Coated Grain: Short Edge</p> <p>Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 60 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex</p> <p>Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF</p>	Side 1 = 60	<p>4 Point Curl - PASSED Simplex = Flat / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel.</p> <p>The Custom Paper Profile setting of 'IG' for side 1 is near the lowest transfer capability (limited to no latitude) for this device.</p> <p>Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80%.</p> <p>Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Adhesives*	Lasergloss HS	Gloss	White	184	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 184gsm Coating: Coated Grain: Short Edge</p> <p>Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex</p> <p>Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF</p>	Side 1 = 70	<p>4 Point Curl - PASSED Simplex = 5mm AI (calms to 'Flat') / Duplex = N/A Coated Side 1 Image Quality = CAUTION Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel.</p> <p>Moderate levels of mottle were observed in some solid area colours observed and in halftones of 80% despite applying a 'Custom Paper Profile'.</p> <p>Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Adhesives*	Lasersilk HS	Silk	White	189	<p>Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 189gsm Coating: Coated Grain: Short Edge</p> <p>Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 70 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex</p> <p>Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF</p>	Side 1 = 70	<p>4 Point Curl - CAUTION Simplex = 6.25mm AI / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight Levels</p>	<p>Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel.</p> <p>Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80%.</p> <p>Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.</p>	●
Adhesives*	PE Laser	Plain	White	224	<p>Media Weight Machine Setting: Coated 221 – 256gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 224gsm Coating: Coated Grain: Short Edge</p> <p>Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 80 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex</p> <p>Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF</p>	Side 1 = 80	<p>4 Point Curl - FAIL Simplex = 33.5mm TI / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = CAUTION Duplex Stacking = N/A Contamination = PASSED w / Slight Levels</p>	<p>Despite applying various Decurler settings, the best achievable Simplex Curl measured 33.5mm, which is beyond the upper curl limits expected for this device.</p> <p>Excessive curl would likely lead to pre-mature 'Output Tray Full' messages, a loss in productivity and possible reliability issues on longer runs. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel.</p> <p>Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80%. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. High simplex curl and minor levels of static were present in the imaged output which may have an effect on Stacking the media on longer runs.</p>	○

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 ○ : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Adhesives*	Polylaser gloss clear	Gloss	Gloss clear	191	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 191gsm Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 120 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF	Side 1 = 120	4 Point Curl - PASSED Simplex = Flat / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = PASSED Duplex Stacking = N/A Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80%. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Moderate levels of static were present in the imaged output which may have an effect on Stacking the media on longer runs.	●
Adhesives*	Polylaser matt transparent HS	Matt	Matt transparent	176	Media Weight Machine Setting: Coated 151 – 176gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 176gsm Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF	Side 1 = 90	4 Point Curl - PASSED Simplex = 3.25mm TI / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = CAUTION Duplex Stacking = N/A Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80%. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Moderate levels of static were present in the imaged output which may have an effect on Stacking the media on longer runs.	●
Adhesives*	Polylaser matt white HS	Matt	Matt white	195	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 195gsm Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 110 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = N/A / IOT Setting = N/A / Finisher Setting = N/A Face Up / Down Output Orientation: Simplex = Face Up LEF / SEF: SEF	Side 1 = 110	4 Point Curl - CAUTION Simplex = 9.25mm TI / Duplex = N/A Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = CAUTION Duplex Stacking = N/A Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80%. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. Moderate levels of static were present in the imaged output which may have an effect on Stacking the media on longer runs.	●
* Size tested : A3									
Paper/Plastic/Paper	PaperTyger	Plain	White	100	Media Weight Machine Setting: Uncoated 91 – 105gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 100gsm (100gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 90 / Side 2 = 100 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 90 Side 2 = default	4 Point Curl - PASSED Simplex = Flat / Duplex = Flat/Uncoated Side 1 Image Quality = PASSED/Uncoated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = CAUTION Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. All were related to in ream static despite fanning the media vigorously prior to placing it in the Feed Tray (strongly recommended). Reliability may improve if run in the Coated 106 - 128gsm run mode (slightly higher basis weight run mode than the test media basis weight of 100gsm). Severe levels of static were present in the simplex imaged output.	○
Paper/Plastic/Paper	PaperTyger	Plain	White	150	Media Weight Machine Setting: Coated 129 – 150gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 150gsm (150gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 130 / Side 2 = 110 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Left Button - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 130 Side 2 = 110	4 Point Curl - PASSED Simplex = 4mm TI / Duplex = 1mm AI Coated Side 1 Image Quality = PASSED Coated Side 2 Image Quality = PASSED Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '130' for side 1 is near the highest transfer capability (limited latitude) for this device. Minor levels of mottle were observed in some solid area colours and moderate levels observed in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●
Paper/Plastic/Paper	PaperTyger	Plain	White	200	Media Weight Machine Setting: Coated 177 – 220gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 200gsm (200gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 150 / Side 2 = 150 Output Destination: Finisher Stacker Tray Simplex / Duplex: Simplex & Auto Duplex Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Simplex = Face Down / Duplex = Face Face Up / Down Output Orientation: Down LEF / SEF: SEF	Side 1 = 150 Side 2 = 150	4 Point Curl - PASSED Simplex = 2mm TI / Duplex = 1mm TI Coated Side 1 Image Quality = CAUTION Coated Side 2 Image Quality = CAUTION Toner Adhesion = PASSED Both Sides Simplex Stacking = PASSED Duplex Stacking = PASSED Contamination = PASSED w / Slight Levels	Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. The Custom Paper Profile setting of '150' for side 1 & side 2 is at the highest transfer capability (no latitude) for this device. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less despite applying a Custom Paper Profile. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent.	●

Xerox® 700/700i/770 Digital Colour Press - Antalis Media Compatibility Matrix (MCM) - Europe - July 2015

The Antalis Media Compatibility Matrix (MCM) contains paper and specialty media distributed by Antalis, that have gone through special testing by Xerox®. Based on such testing any paper and print media that is featured on the MCM with a "G" rating for a specific Xerox® printer or digital press will give excellent print results using standard settings for optimized performance and will carry the 100% Performance Guaranteed. Some media may require prior testing, as printing results depend on print jobs as indicated in this list.

G : Certified with excellent printing results using default settings
 ● : Certified with excellent print results using specific settings for optimized performance
 ○ : Prior testing is recommended, printing results depend on print job
 o : Not recommended
 Size tested : SRA3

Type	Media Name	Finish	Colour	Weight (g/m2)	Optimum Settings	Transfer	Observations Toner adhesion and Image Quality	Comments	Lab results Summary
Paper/Plastic/Paper	PaperTyger	Plain	White	296	<p>Media Weight Machine Setting: Coated 257 – 300gsm Trays: Tray 6 (OHCF) Actual Media Basis Weight: 296gsm (296gsm Listed on Box) Coating: Coated Grain: Short Edge Custom Paper Profile Setting Side 1 / Side 2: Side 1 = 100 / Side 2 = 100 Output Destination: Finisher Top Output Tray Simplex / Duplex: Simplex & Auto Duplex (manual duplex on some systems) Simplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto - See Comments Duplex Decurler Settings: Tray Curl Properties = Default / IOT Setting = Auto / Finisher Setting = Auto Face Up / Down Output Orientation: Simplex = Face Up / Duplex = Face Up LEF / SEF: SEF</p>	Side 1 = Default Side 2 = Default	4 Point Curl - FAIL Simplex = 25mm TI / Duplex = N/A Coated Side 1 Image Quality = FAIL Coated Side 2 Image Quality = N/A Toner Adhesion = PASSED One Side Simplex Stacking = N/A Duplex Stacking = N/A Contamination = N/A	Despite applying various Decurler settings, the best achievable Simplex Curl measured 25mm, which is beyond the upper curl limits expected for this device. Excessive curl would likely lead to pre-mature 'Output Tray Full' messages, a loss in productivity and possible reliability issues on longer runs. Decurler settings adjusted via the Custom Paper Profile found in the 'Machine Status' menu, 'Tools' tab of the User Interface, at the IOT Decurler Control Panel and / or the Finisher Decurler Control Panel. Moderate levels of mottle were observed in some solid area colours and in halftones of 80% and less. Mottle levels will vary and are media, file, colour, application, area coverage, environmental and DFE (digital front end) dependent. In addition, image defects, in the form 'banding', were observed on the imaged output.	○