2007 F-SERIES SUPER DUTY° F-350/F-450/F-550 CHASSIS CABS





Moves like a Fullback

Here's a truck that knows how to make the big plays — moving heavy loads into tight places. F-Series Super Duty Chassis Cabs can deliver GCWRs up to 33,000 lbs., crushing horsepower and torque, plus outstanding maneuverability. Ford Chassis Cabs have built their reputations on rugged construction, huge capacities, easy upfits and comfort for drivers and crews alike. When you add agility that would make a first-round draft pick jealous, it's easy to see why this player has helped make F-Series the best-selling line of trucks for 29 years running.

Powerful choices

- 6.0L Power Stroke® V8 Turbo Diesel
- 6.8L 3-Valve Triton® V10 with Bestin-Class Horsepower and Gas Torque
- 5.4L 3-Valve Triton V8
- TorqShift® 5-Speed Automatic with Tow/Haul Mode
- 6-Speed Manual Transmission

Exclusive features

- TowCommand Integrated Electric Trailer Brake Controller Option
- Standard Auxiliary Upfitter Switches

SPECIFICATIONS

SPECIFICATIONS

STANDARD FEATURES

SAFETY/SECURITY

Airbags1 - Driver and right-front passenger

Alert chimes — Headlamps-on, key-in-ignition and door ajar

Belt-Minder® safety belt reminder

 ${\sf BlockerBeam}^{\tiny{\circledR}}-{\sf Front\ bumper\ underride\ protection\ system}$

Brake/shift interlock (with automatic transmission)

Child-safety seat top tether anchors (front-passenger seat on Regular Cab; all rear seats on SuperCab and Crew Cab)

Fuel pump inertia shutoff switch

Height-adjustable safety belts — Front outboard (Regular Cab,

XL SuperCab, Crew Cab)

Passenger airbag deactivation switch (Regular Cab, SuperCab)

 ${\bf Safety\ belt\ energy-management\ retractors-Front-outboard\ positions}$

Side-intrusion door beams

MECHANICAL

5.4L SOHC 3-valve Triton® V8 engine (F-350 SRW)

6.8L SOHC 3-valve Triton V10 engine (F-350 DRW/F-450/F-550)

6-speed manual overdrive transmission with Power TakeOff (PTO) provision (F-350/F-450; PTO obstructed by catalyst placement on 5.4L engine; 6.8L engine with manual transmission may require exhaust pipe re-routing to fit aftermarket PTO)

TorqShift® 5-speed automatic overdrive transmission (F-550)

100,000-mile tune-up interval² (gas engines)

Battery saver

Fail-safe engine cooling system (gas engines)

Fuel tank — 40-gallon capacity (includes auxiliary fuel tap)

Manual 4-wheel-drive system with manual locking hubs (4x4 models only)

Power 4-wheel disc brakes with ABS

Power steering

Stabilizer bars — Front and rear

Stainless steel exhaust system (major components)

Stationary Elevated Idle Control (SEIC) (final-stage manufacturer must supply control switches)

Steering damper

Trailer tow prep - 7-wire harness (blunt cut) with relays

INTERIOR

Assist and ride handles

Coat hooks - 2

Cupholders -2 on instrument panel (2 in rear with XLT/LARIAT SuperCab and XLT/LARIAT Crew Cab)

Dome light (front and rear with Crew Cab)

Flip-open rear quarter windows (SuperCab)

Instrumentation — Engine-hour meter, speedometer, tachometer, trip odometer, voltmeter (man. trans.), oil pressure, coolant temperature, transmission temperature gauge (auto. trans.), air filter minder (diesel only), fuel gauge, indicator lights and turbo boost (diesel only)

Power points – 2 on instrument panel (including lighter)

Steering wheel - Black vinyl

Upfitter switches - 4

EXTERIOR

Bumper - Front, painted

Front fender moldings with integrated mud flaps (F-450/F-550)

Roof clearance lights

Solar-tinted glass

Tow hooks - Front (2)

Windshield wipers - Interval

¹Always wear your safety belt and always deactivate the passenger airbag when using a rear-facing child-safety seat with Regular Cab and SuperCab models. Always wear your safety belt and always secure children in the rear seat with Crew Cab models. Passenger airbag may be deleted. ²Under normal driving conditions with routine fluid and filter changes.

Comparisons based on 2007 competitive models, publicly available information and Ford certification data at time of printing. Some features discussed may be optional. Vehicles throughout this catalog are shown with optional and aftermarket upfit equipment. Features shown may be offered only in combination with other options or subject to additional ordering requirements or limitations. Dimensions and capacity ratings shown may vary due to optional features and/or production variability. Following publication of the catalog, certain changes in standard equipment, options and the like, or product delays may have occurred which would not be included in these pages. Your Ford Dealer is the best source for up-to-date information. Ford Division reserves the right to change product specifications at any time without incurring obligations. Body manufacturers are responsible for compliance certification of the completed vehicle. The Ford New Vehicle Limited Warranty and any government certification made by Ford shall cover only the vehicle as manufactured by Ford and shall not extend to any addition, modification or change of or to the vehicle by the Ford Authorized Pool Account.

FFATURES & OPTIONS

- E <i>F</i>	ATU	RES	S & OPTIONS ——————————————
			XL
			XLT
			LARIAT
			SAFETY/SECURITY
_	0	•	Advanced Security Group — Includes autolock, autolamp, illuminated entry system, driver's-door keypad and remote keyless-entry system with 2 key fobs
			MECHANICAL
•			
0	0	0	5.4L SOHC 3-valve Triton V8 engine (F-350 only) 6.8L SOHC 3-valve Triton V10 engine
0		0	6.0L OHV 32-valve Power Stroke® V8 Turbo Diesel engine
•		•	6-speed manual overdrive transmission with Power TakeOff (PTO) provision
			(F-350/F-450; PTO obstructed by catalyst placement on 5.4L engine; 6.8L engine with manual transmission may require exhaust pipe re-routing to fit aftermarket PTO)
•	0	•	6-speed manual overdrive transmission with Power TakeOff (PTO) provision (optional on F-550; PTO obstructed by catalyst placement on 5.4L engine; 6.8L engine with manual transmission may require exhaust pipe re-routing to fit aftermarket PTO)
0	0	0	Power TakeOff (PTO) provision — Automatic transmission with 6.8L or 6.0L engine
0	0	0	TorqShift 5-speed automatic overdrive transmission with Tow/Haul Mode
0	0	0	Electronic Shift-On-the-Fly 4-wheel-drive system with auto/manual locking hubs (F-350 4x4 models only)
•	_	_	18" steel wheels (F-350 SRW)
_	•	_	18" chromed-steel wheels (F-350 SRW)
_	0	_	18" forged polished-aluminum wheels (F-350 SRW)
_ _ •	_	•	18" premium polished-aluminum wheels (F-350 SRW)
• -	•	_	17" steel wheels — 6 (F-350 DRW) 17" forged polished-aluminum wheels — 4 (F-350 DRW)
	0	•	17 forged polished-aluminum wheels — 4 (F-350 DRW) 19.5" steel wheels — 6 (F-450/F-550)
•	0	•	19.5 steel wheels — 6 (F-450/F-550) 19.5" forged polished-aluminum wheels — 4 (F-450/F-550)
•		•	LT275/65R18 all-season BSW tires (F-350 SRW 4x2)
•			LT275/708118 all-season BSW tires (F-350 SRW 4x4)
0	0		LT275/70R18 all-terrain BSW tires (F-350 SRW 4x4)
_	Ŏ	ō	LT275/70R18 all-terrain OWL tires (F-350 SRW 4x4)
•	•	•	LT245/75R17 all-season BSW tires — 6 (F-350 DRW)
0	0	0	LT245/75R17 all-terrain BSW tires — 6 (F-350 DRW)
_	0	0	LT245/75R17 all-terrain OWL tires — 4 (F-350 DRW) ³
•	•	•	225/70R19.5F all-season BSW tires (F-450/F-550)
0	0	0	225/70R19.5F traction BSW tires — 4 rear only (F-450/F-550)
0	0	0	225/70R19.5F max. traction BSW tires — 6 (F-450/F-550 4x4 only)4
0	0	0	225/70R19.5G all-position BSW tires — 6 (F-450/F-550; late availability)
0	0	0	Engine block heater ⁵
0	0	0	Extra-heavy-duty alternator — 140-amp (diesel engine only)
0	0	0	Dual alternators — 260-amp (diesel engine only)
0	0	0	Fuel tank — 19-gallon capacity midship in place of standard (DRW models only with some exclusions) Fuel tanks — 59-gallon capacity dual tank combination: 40-gallon aft-of-axle standard
0	0	0	plus 19-gallon midship (DRW models with diesel engine only) Higher-ratio rear axle (excludes 6.0L-equipped SRW models)
0	0	0	Limited-slip rear axle
0	0	0	Skid plate – Transfer case (SuperCab and Crew Cab 4x4 models only)
0	0	0	Spare tire and wheel — Includes jack
0	0	0	TowCommand Integrated Trailer Brake Controller (not available with Trailer Tow Package; replaces standard Trailer Tow Package on LARIAT; electric brakes only)
0	0	0	Vehicle jack SEATING
•	_		Front bench seat – HD vinyl (not available with Crew Cab)
0	_	_	Front bench seat — HD vinyl weave (standard with Crew Cab)
0	_	_	Front bench seat — HD cloth
0	•	•	Front bench seat — 40/20/40 split with armrest, cupholders and storage bin (XL - HD vinyl or HD cloth; XLT - cloth; LARIAT - leather-trimmed)
0		_	Front bucket seats — HD vinyl
0	_		Front bucket seats – HD vinyl weave
0	_	<u> </u>	Front bucket seats — HD cloth
.		• 0	loot Availability O Optional Not Available

³Inner tire is BSW. ⁴Not recommended for over-the-road application. ⁵Standard in select cold-weather states

FEATURES & OPTIONS (continued)

			XL
			XLT
			LARIAT
			SEATING (continued)
_	0		Front captain's chairs with console (XLT – cloth; LARIAT – leather trim)
_		0	Heated seats — Driver and front-passenger
_	•	•	Lumbar support — Driver and front-passenger
_	0	•	Power 6-way driver and front-passenger seats (passenger seat with
			Crew Cab only)
•	•	•	Rear fold-up bench seat (SuperCab; vinyl rear bench on XL and LARIAT
•	_	-	Rear bench with folding seatback (Crew Cab)
_	•	•	Rear FlexFold™ 60/40 split bench seat, fold-flat feature with solid-steel
			loadfloor, grocery hooks, dual integrated cupholders and tray, and outboard head restraints (Crew Cab)
0			Rear-seat delete (SuperCab)
		_	Medi-seat delete (Super Cab)
			INTERIOR
0	•	•	Accessory delay for power features ¹
0	•	_	Air conditioning — Manual
_	-	•	Air conditioning — Electronic Automatic Temperature Control (EATC)
•	—	-	AM/FM stereo with digital clock
0	•	•	AM/FM stereo with single-CD player and digital clock
_	0	0	AM/FM stereo with 6-disc in-dash CD changer and digital clock
0	•	•	Cruise control
•	0	0	Driver's-side glove compartment (requires automatic transmission; 4x4 requires ESOF)
•			Floor covering — Black vinyl
_		•	Floor covering — Black Viriyi Floor covering — Carpet
_		•	Floor mats — Color-coordinated
_	0	0	Floor mats — Black all-weather
•	•	_	Instrument cluster — Black with black gauges
_	i i	•	Instrument cluster — Bronze-faced with cream gauges
_	_	•	Instrumentation pack with enhanced message center
_	-	•	Overhead console with sunglasses storage and garage door opener storage (SuperCab and Crew Cab)
_	0	0	Power-adjustable brake and accelerator pedals (with automatic transmission only)
•	•	•	Power door locks ¹
•	•	•	Power front windows with one-touch-down driver's-side feature ¹
			(includes power rear windows on Crew Cab)
0	_	-	Radio delete
•	•	_	Rearview mirror — Day/night
_	-	•	Rearview mirror — Auto-dimming
		•	Secondary steering wheel-mounted audio/climate controls
_	0	0	Steering wheel – Black leather-wrapped
0	-	•	Storage tray — Behind seat Tilt steering wheel
_			Visors with passenger mirror
_		•	Visors with illuminated driver and passenger mirrors
_	<u> </u>	•	Woodgrain-style instrument-panel insert
		—	
			EXTERIOR
•	-	-	Bumper – Front, argent-painted
•	•	•	Bumper – Front, chrome ²
0	0	•	Cab steps — Black molded
0	0	0	Daytime running lamps (Fleet only)
•	<u> </u>	<u> </u>	Grille – Black
_	•	•	Grille – Bright
•	<u> </u>	-	Headlamps – Sealed-beam halogen
0	•	•	Headlamps — Dual-beam jewel-effect ²
0	•	•	Light – Underhood service ²
•	_	_	Mirrors — Manual glass, manual telescoping trailer tow with 2-way fold
•	•	•	Mirrors¹ – Power glass, manual telescoping trailer tow with 2-way fold (also heated glass, integrated turn signals and clearance lights)
_	0	•	Privacy glass (rear doors and rear window) ³
_	6	•	Sliding rear window – Manual

¹Included as part of Power Equipment Group. ²Included as part of the XL Décor Group. ³Requires sliding rear window.

EQUIPMENT PACKAGES -

			XL
			XLT
			LARIAT
0	0	0	15,000-lbs. GVWR Package (F-450 only)
0	0	0	Ambulance Prep Package ⁴ (requires diesel engine) — Includes air conditioning, dual alternators (combined 260 amps), standard-width axle included with F-350 SRW, wide-track 4.10 limited-slip axle included with F-350 DRW, and maximum front spring/GAWR on all models
0	_	_	Convenience Package – Includes cruise control, tilt steering wheel, air conditioning, and AM/FM stereo with single-CD player and digital clock
0	0	0	Heavy-Service Suspension Package ⁵ — Includes 1-up heavy-service front springs (150-lb. upgrade — 4x2; 400-lb. upgrade — 4x4; not available if maximum spring is selected as standard)
0	0	0	Extra-Heavy-Service Suspension Package ⁵ — Includes 2-up extra-heavy-service front springs (300-lb. upgrade — 4x2; 800-lb. upgrade — 4x4; not available if maximum spring is selected as standard)
0	0	0	High-Capacity Trailer Tow Package (F-450/F-550 with diesel engine) — Includes 28,000 lbs. GCWR with F-450/F-550 6-speed manual transmission; 30,000 lbs. GCWR with F-450 with TorqShift®; and 33,000 lbs. GCWR with F-550 with TorqShift and upgraded 4.88 rear axle gear set
0	0	0	Low Deflection Package (recommended for rear-biased loading) — Includes 2" spacer blocks (F-450/F-550 only; excludes 140.8" wheelbase)
•	0	0	Payload Upgrade Package – Increases GVWR for increased payload range (F-350 SRW and F-550 only)
0	•	•	Power Equipment Group — Includes power locks, power front windows with one-touch-down driver's-side feature (includes power rear windows on Crew Cab) and power sideview mirrors
0	0	0	Snow Plow Prep Package ⁵ — Includes specific spring/GAWR upgrade ranging from 5200–7000 lbs. (depending on model), 140-amp alternator and unique fan clutch with 6.0L diesel (4x4 only on F-350)
0	0	•	Trailer Tow Package — Includes trailer brake wiring kit ready for aftermarket upfit (no controller)
0	_	_	XL Décor Group – Includes chrome front bumper, dual-beam jewel-effect headlamps and underhood service light; also includes bright hub covers and center ornaments on F-350 SRW

⁴Restrictions and special instructions apply. See your Ford Dealer for information. ⁵Option and other restrictions apply. See your Ford Dealer for information.

INTERIOR DIMENSIONS -

	DECLUAD CAD	OUDEDOAD	ODEW OAD
	REGULAR CAB	SUPERCAB	CREW CAB
FRONT			
Head room	41.1"	41.4"	41.3"
Shoulder room	68.0"	68.0"	68.0"
Hip room	67.4"	67.4"	67.4"
Leg room	41.0"	41.0"	41.0"
Volume (cu. ft.)	66.3	66.8	66.6
REAR			
Head room	_	38.2"	40.8"
Shoulder room	_	68.0"	68.0"
Hip room	_	67.3"	67.3"
Leg room	_	32.2"	41.7"
Volume (cu. ft.)	_	48.4	67.0
Total volume (cu. ft.)	66.3	115.2	133.6

MAXIMUM LOADED TRAILER WEIGHT (LBS.)

REGULAR CAB						
	AXLE	GCWR	F-350	F-350	F-350	F-350
ENGINE	RATIO 3.73	(LBS.)	4x2 SRW	4x4 SRW	4x2 DRW ¹	4x4 DRW
5.4L 3-Valve Triton® V8	3.73 4.10	15,000 17,000	8500 10,500	8100 10,100	8200 —	7800 —
		17,500			10,700	10,300
6.8L 3-Valve	4.10	20,000	13,400	13,000		
Triton V10	4.30	20,500 22,500	_	_	13,600 15,600	13,200 15,200
6.0L Power Stroke®	3.73	23,000	15.900	15,400		
V8 Turbo Diesel		23,500	_	_	16,100	15,700
	4.10	23,500	_	_	16,100	15,700
	AXLE	GCWR	F-450	F-450	F-550	F-550
ENGINE	RATIO	(LBS.)	4x2 DRW1	4x4 DRW1		4x4 DRW
6.8L 3-Valve Triton V10	4.88 5.38	26,000 26,000	18,400 18,400	18,000 18,000	18,300 18,300	18,000 18,000
6.0L Power Stroke	4.30	26,000	18,000	17,600		
V8 Turbo Diesel	4.88	26,000	18,000	17,600	17,900	17,600
		28,000²	20,000	19,600	19,900	19,600
SUPERCAB						
FNOINE	AXLE	GCWR	F-350	F-350	F-350	F-350
ENGINE	RATIO	(LBS.)	4x2 SRW	4x4 SRW	4x2 DRW	4x4 DRW
5.4L 3-Valve Triton V8	3.73 4.10	15,000 17,000	8200 10,200	7700 9700	_	_
6.8L 3-Valve	4.10	20,000	13,000	12,600	_	_
Triton V10		20,500	_	_	13,300	12,800
	4.30	22,500	_	_	15,300	14,800
6.0L Power Stroke V8 Turbo Diesel	3.73	23,000 23,500	15,500	15,100	— 15,700	 15,300
VO TUIDO DICSCI	4.10	23,500	_	_	15,700	15,300
	AXLE	GCWR	F-450	F-450	F-550	F-550
ENGINE	RATIO	(LBS.)	4x2 DRW1	4x4 DRW1	4x2 DRW1	4x4 DRW
6.8L 3-Valve	4.88	26,000	18,000	17,700	18,000	17,600
Triton V10	5.38	26,000	18,000	17,700	18,000	17,600
6.0L Power Stroke V8 Turbo Diesel	4.30 4.88	26,000 26,000	17,600 17,600	17,300 17,300	— 17,500	17,200
		28,000 ²	19,600	19,300	19,500	19,200
CREW CAB						
	AXLE	GCWR	F-350	F-350	F-350	F-350
ENGINE	RATIO	(LBS.)	4x2 SRW	4x4 SRW	4x2 DRW	4x4 DRW
5.4L 3-Valve Triton V8	3.73 4.10	15,000	8000	7500	_	_
	4 111	17,000	10,000	9500 12,400		
		20 000	1.7 81111			
6.8L 3-Valve	4.10	20,000 20,500	12,800 —		13,100	12,600
6.8L 3-Valve Triton V10			12,800 — —	— —	13,100 15,100	12,600 14,600
6.8L 3-Valve Triton V10 6.0L Power Stroke	4.10	20,500 22,500 23,000	12,800 — — — 15,300	14,800	15,100 —	14,600
6.8L 3-Valve Triton V10 6.0L Power Stroke	4.10 4.30 3.73	20,500 22,500 23,000 23,500	<u> </u>	<u> </u>	15,100 — 15,500	14,600 — 15,100
6.8L 3-Valve Triton V10 6.0L Power Stroke	4.10 4.30	20,500 22,500 23,000	<u> </u>	<u> </u>	15,100 —	14,600
6.8L 3-Valve Triton V10 6.0L Power Stroke V8 Turbo Diesel	4.10 4.30 3.73 4.10 AXLE RATIO	20,500 22,500 23,000 23,500 23,500 GCWR (LBS.)	15,300	14,800	15,100 — 15,500 15,500 F-550	14,600 — 15,100 15,100 F-550 4x4 DRW
6.8L 3-Valve Triton V10 6.0L Power Stroke V8 Turbo Diesel ENGINE 6.8L 3-Valve	4.10 4.30 3.73 4.10 AXLE RATIO 4.88	20,500 22,500 23,000 23,500 23,500 GCWR (LBS.) 26,000	15,300 — F-450 4x2 DRW ¹	14,800 — F-450 4x4 DRW ¹	15,100 — 15,500 15,500 F-550 4x2 DRW ¹ 17,800	14,600 — 15,100 15,100 F-550 4x4 DRW 17,400
6.8L 3-Valve Triton V10 6.0L Power Stroke V8 Turbo Diesel ENGINE 6.8L 3-Valve Triton V10	4.10 4.30 3.73 4.10 AXLE RATIO 4.88 5.38	20,500 22,500 23,000 23,500 23,500 GCWR (LBS.) 26,000 26,000	15,300 — — F-450 4x2 DRW ¹ 17,800 17,800	14,800 — — F-450 4x4 DRW ¹ 17,500 17,500	15,100 — 15,500 15,500 F-550 4x2 DRW ¹	14,600 — 15,100 15,100 F-550 4x4 DRW
6.8L 3-Valve Triton V10 6.0L Power Stroke V8 Turbo Diesel ENGINE 6.8L 3-Valve	4.10 4.30 3.73 4.10 AXLE RATIO 4.88	20,500 22,500 23,000 23,500 23,500 GCWR (LBS.) 26,000	15,300 — F-450 4x2 DRW ¹	14,800 — F-450 4x4 DRW ¹	15,100 — 15,500 15,500 F-550 4x2 DRW ¹ 17,800	14,600 — 15,100 15,100 F-550 4x4 DRW 17,400

F-350 DRW/F-450/F-550 weights shown are for 141" wheelbase Regular Cab or 176" wheelbase Crew Cab models.
For 165," 189," 200" and 201" wheelbase models, weights may be somewhat less (usually not more than 200 lbs., or
400 lbs with 201" wheelbase)

²Available with High-Capacity Trailer Tow Package only.

	_					
REGULAR CAB						
ENGINE	AXLE RATIO	GCWR (LBS.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW ¹	F-350 4x4 DRW
5.4L 3-Valve Triton V8	3.73	16,000 16.500	9500 —	9100	— 9700	— 9300
	4.10	18,000 18,500	11,500 —	11,100 —	— 11,700	— 11,300
6.8L 3-Valve Triton V10	4.10	21,000 21,500	14,500	14,000	— 14,700	— 14,200
	4.30	23,000			16,200	15,700
6.0L Power Stroke V8 Turbo Diesel	3.73	23,000 23,500	15,900 —	15,500 —	— 16,200	— 15,700
	4.10	23,500			16,200	15,700
ENGINE	AXLE RATIO	GCWR (LBS.)	F-450 4x2 DRW ¹	F-450 4x4 DRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW
6.8L 3-Valve Triton V10	4.88 5.38	26,000 26,000	18,400 18,400	18,100 18,100	18,400 18,400	18,000 18,000
6.0L Power Stroke V8 Turbo Diesel	4.30 4.88	26,000 26,000 30.000 ²	18,000 18,000 22.000	17,700 17,700 21,700	17,900 17,900	17,600 17,600
		33,000 ²			24,900	24,600
SUPERCAB						
ENGINE	AXLE RATIO	GCWR (LBS.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRV
5.4L 3-Valve Triton V8	3.73	16,000 18,000	9100 11,100	8700 10,700	_	_
6.8L 3-Valve	4.10	21,000	14,100	13,600	-	
Triton V10		21,500	_	_	14,300	13,800

	23,500	_	_	15,800	15,300
4.10	23,500	_	_	15,800	15,300
AXLE RATIO	GCWR (LBS.)	F-450 4x2 DRW ¹	F-450 4x4 DRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW ¹
4.88 5.38	26,000 26,000	18,000 18,000	17,700 17,700	18,000 18,000	17,700 17,700
4.30 4.88	26,000 26,000 30,000 ²	17,600 17,600 21,600	17,300 17,300 21,300	17,600 17,600 —	17,300 17,300 — 24,300
	AXLE RATIO 4.88 5.38 4.30	AXLE GCWR RATIO (LBS.) 4.88 26,000 4.30 26,000 4.88 26,000	A,10 23,500 —	23,500	A,10

15,600

15,100

15,800

15,300

4.30

3.73

6.0L Power Stroke

23,000

23,000

		00,000			2 1,000	2 1,000
CREW CAB						
ENGINE	AXLE RATIO	GCWR (LBS.)	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW
5.4L 3-Valve Triton V8	3.73 4.10	16,000 18,000	8900 10,900	8500 10,500	_	_
6.8L 3-Valve Triton V10	4.10 4.30	21,000 21,500 23,000	13,900 — —	13,400 — —	— 14,100 15,600	— 13,600 15,100
6.0L Power Stroke V8 Turbo Diesel	3.73 4.10	23,000 23,500 23,500	15,400 — —	14,900 — —	 15,600 15,600	15,100 15,100
ENGINE	AXLE RATIO	GCWR (LBS.)	F-450 4x2 DRW ¹	F-450 4x4 DRW ¹	F-550 4x2 DRW ¹	F-550 4x4 DRW ¹
6.8L 3-Valve Triton V10	4.88 5.38	26,000 26,000	17,800 17,800	17,500 17,500	17,800 17,800	17,400 17,400
6.0L Power Stroke V8 Turbo Diesel	4.30 4.88	26,000 26,000 30,000 ² 33,000 ²	17,400 17,400 21,400	17,100 17,100 21,100	17,400 17,400 — 24,400	17,000 17,000 — 24,000

Note: 5th-wheel trailer weights shown. See your Ford Dealer for conventional trailer weights.

Note: Trailer weights shown assume 1000 lbs, second-unit body weight. Be sure combined weight of vehicle and trailer does not exceed listed GCWR. Trailer kingpin weight should be 15-25% of total loaded trailer weight. Make sure that the vehicle payload (reduced by option weight) will accommodate trailer kingpin weight and the weight of passengers and cargo added to the towing vehicle. The addition of trailer kingpin weight, and the weight of passengers and cargo cannot cause vehicle weights to exceed the rear GAWR (Gross Axle Weight Rating) or GVWR (Gross Vehicle Weight Rating). These ratings can be found on the vehicle's Safety Compliance Certification Label.

WEIGHTS & DIMENSIONS

REGULAR CA	3										
	F-350 SRW	F-350 DRW	F-350 DRW	F-450 DRW	F-450 DRW	F-450 DRW	F-450 DRW	F-550 DRW	F-550 DRW	F-550 DRW	F-550 DRW
Wheelbase (in.)	140.8	140.8	164.8	140.8	164.8	188.8	200.8	140.8	164.8	188.8	200.8
. ,											
Cab-to-axle (in.)	60	60	84	60	84	108	120	60	84	108	120
Max. GVWR (lbs		10.000	10.000	10.000	10.000	10.000	10.000	17050	10.000	17.050	10.000
4x2 4x4	10,700 11.000	13,000 13.000	13,000 13.000	16,000 16,000	16,000 16.000	16,000 16.000	16,000 16.000	17,950 17,950	19,000 19.000	17,950 17.950	19,000 19.000
	,	13,000	13,000	10,000	10,000	10,000	10,000	17,950	19,000	17,950	19,000
Max. payload (lb 4x2	s.J 4800	7400	7300	9500	9400	9100	9100	11.400	12.300	11.000	12,000
4x2 4x4	4700	6900	6800	9200	9100	8800	8800	11,400	12,300	10.700	11,700
Overall length (in		225.6	249.6	225.6	249.6	273.6	285.6	225.6	249.6	273.6	285.6
	•			223.0	249.0	2/3.0	200.0	223.0	249.0	2/3.0	200.0
Top of cab to gro 4x2	una — Er 76.9	npty (in.) 77.1	76.9	80.6	80.5	80.5	80.2	81.7	81.4	81.4	81.1
4x2 4x4	76.9 81.6	80.0	80.2	80.7	80.5	80.5	80.2	81.7	81.2	81.1	80.7
Top of frame to g						00.0	00.0	01.7	01.2	01.1	00.7
4x2	32.7	33.1	32.8	11pty (111.) 32.3	32.3	32.2	32.2	32.2	32.2	32.2	32.2
4x4	34.5	34.9	34.6	32.3	32.4	32.3	32.3	32.3	32.3	32.2	32.2
Width between	34.1	34.1	34.1	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
frame rails (in.)	34.1	34.1	34.1	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
Axle clearance (i	n.)										
4x2	8.8	8.7	8.7	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
4x4	9.3	8.7	8.7	8.0	8.0	8.0	8.0	8.0	8.0	8.0	8.0
Front tread width	(in.)										
4x2	68.3	68.9	68.9	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
4x4	68.3	69.0	69.0	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
Rear tire outside	width (in	ı.)									
4x2	79.5	92.2	92.2	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6
4x4	79.5	92.2	92.2	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6

SUPERCAB				
	F-350 SRW	F-350 DRW	F-450 DRW	F-550 DRW
Wheelbase (in.)	161.8	161.8	161.8	161.8
Cab-to-axle (in.)	60	60	60	60
Max. GVWR (lbs.) 4x2/4x4	11,000/11,400	13,000	16,000	17,950
Max. payload (lbs.) 4x2/4x4	4800/4700	6900/6400	9100/8800	11,000/10,700
Overall length (in.)	246.6	246.6	246.6	246.6
Top of cab to ground — Empty (in.)				
4x2	77.4	77.4	80.5	81.5
4x4	81.5	80.2	80.5	81.3
Top of frame to ground at end of fra	ame – Empty (in.)			
4x2	32.3	32.8	32.3	32.3
4x4	34.2	34.6	32.3	32.3
Width between frame rails (in.)	34.1	34.1	34.2	34.2
Axle clearance (in.) 4x2/4x4	8.8/9.3	8.7	8.1	8.1
Front tread width (in.) 4x2/4x4	68.3	68.9/69.0	74.8	74.8
Rear tire outside width (in.)	79.5	92.2	93.6	93.6

	F-350 SRW	F-350 DRW	F-450 DRW	F-450 DRW	F-550 DRW	F-550 DRW
Wheelbase (in.)	176.2	176.2	176.2	200.2	176.2	200.2
Cab-to-axle (in.)	60	60	60	84	60	84
Max. GVWR (lbs.) 4x2/4x4	11,200/11,500	13,000	16,000	16,000	17,950	17,950
Max. payload (lbs.) 4x2/4x4	4800/4700	6800/6200	8900/8600	8800/8500	10,800/10,500	10,700/10,400
Overall length (in.)	261.0	261.0	261.0	285.0	261.0	285.0
Top of cab to ground -	- Empty (in.)					
4x2	77.9	77.9	80.8	80.8	81.4	81.4
4x4	81.8	80.8	80.9	80.9	81.3	81.3
Top of frame to ground	at end of frame -	- Empty (in.)				
4x2	32.1	32.6	32.1	32.1	32.2	32.1
4x4	34.1	34.4	32.2	32.2	32.2	32.2
Width between frame ra	ails (in.) 34.1	34.1	34.2	34.2	34.2	34.2
Axle clearance (in.) 4x2	2/4x4 8.8/9.3	8.7	8.0	8.0	8.0	8.0
Front tread width (in.)						
4x2/4x4	68.3	68.9/69.0	74.8	74.8	74.8	74.8
Rear tire outside width	(in.) 79.5	92.2	93.6	93.6	93.6	93.6

MECHANICAL SPECIFICATIONS

				TorgShift®
Model	Engine	4x4 Transfer Case Manual	6-Speed Manual	5-Speed Automatic
F-350 ¹	5.4L 3-Valve Triton® V8	2-speed	•	0
F-350 ¹	6.8L 3-Valve Triton V10	2-speed	0	0
F-350	6.0L Power Stroke® V8 Turbo Diesel	2-speed	0	0
F-450	6.8L 3-Valve Triton V10	2-speed	•	0
F-450	6.0L Power Stroke V8 Turbo Diesel	2-speed	0	0
F-550	6.8L 3-Valve Triton V10	2-speed	0	•
F-550	6.0L Power Stroke V8 Turbo Diesel	2-speed	0	0

● Standard ○ Optional

¹6.8L V10 engine standard with DRW Chassis Cabs. 5.4L V8 optional with DRW Regular Cab. See your Ford Dealer for powertrain availability in California Emissions States.

BRAKES	
Туре	4-wheel disc (standard); 4-wheel ABS (standard)
Front: Rotor diameter	13.66" (F-350); 14.53" (F-450/F-550)
Lining area (sq. in.)	34.9 (F-350); 55.6 (F-450/F-550)
Rear: Rotor diameter	13.39" (F-350); 15.35" (F-450/F-550)
Lining area (sq. in.)	38.2 (F-350); 55.6 (F-450/F-550)

g a. oa (oq)	00.2 (1 000), 00.0 (1 100).
FUEL CAPACITY	
Location/capacity	 Aft-of-rear-axle/40-gallon (standard) Midship/19-gallon (optional in place of 40-gallon tank on DRW models; not available on 188.8"/200.2" wheelbase with gas engines) Midship/19-gallon (optional in addition to 40-gallon tank on DRW models with diesel engine; total 59-gallon capacity)

STEERING	
Туре	Haltenberger linkage (4x2); cross-tie linkage (4x4)
Assist	Power
Overall ratio	20.16:1 (F-350 4x2); 20.38:1 (F-350 4x4); 17.8:1 average (F-450/F-550)

SUSPENSION – FRONT		
Twin-I-Beam (F-350 4x2); Twin-Coil Monobeam solid axle (F-350 4x4, F-450/F-550)		
4850 lbs. (F-350 4x2); 6000 lbs. (F-350 4x4); 7000 lbs. (F-450/F-550)		
Coil		
13/8" gas type		
Standard		

SUSPENSION – REAR		
Туре	Solid axle	
Axle (rating @ ground) GAWR	7280 lbs. (F-350 SRW); 9750 lbs. (F-350 DRW); 12,000 lbs. (F-450); 13,660 lbs. (F-550)	
Springs	Leaf	
Shock absorbers	13/8" gas type	
Stabilizer bar	Standard	

WHEELS	
Туре	Steel (standard); aluminum (optional)
Size	17" DRW, 18" SRW (F-350); 19.5" (F-450/F-550)
Studs	8 (F-350); 10 (F-450/F-550)
Bolt circle diameter	6.7" (F-350 SRW); 7.87" (F-350 DRW); 8.85" (F-450/F-550)

POWERTRAIN SPECIFICATIONS

Configuration	5.4L 3-VALVE TRITON® V8 SOHC	6.8L 3-VALVE TRITON V10 SOHC	6.0L POWER STROKE® V8 TURBO DIESEL OHV (32-valve)
Fuel injection	Sequential electronic	Sequential electronic	Electro-hydraulic w/ Generation 2 fuel injection
Engine control system	Electronic	Electronic	Electronic
Induction system	Specially tuned	Specially tuned	Electronic Variable Response Turbocharger (EVRT TM), intercooler
Battery	12-volt; 750-CCA/78-amp	12-volt; 750-CCA/78-amp	Dual 12-volt; 750-CCA/78-amp
Alternator	115-amp	115-amp	110-amp; optional 140-amp single or 260-amp dual
Cooling system	Pressurized series flow	Pressurized series flow	Pressurized series flow
Cylinders	8	10	8
Cylinder head material	Aluminum	Aluminum	Cast iron
Block material	Cast iron	Cast iron	Cast iron
Valve operation	Hydraulic roller	Hydraulic roller	Push rod/rocker arms
Camshaft drive	Variable cam timing	Silent chain	Gear
Bore	3.55"	3.55"	3.74"
Stroke	4.16"	4.16"	4.13"
Compression ratio	9.8:1	9.2:1	18.0:1
Horsepower (hp @ rpm)	300 @ 5000	362 @ 4750	325 @ 3300
Torque (lbft. @ rpm)	365 @ 3750	457 @ 3250	570 @ 2000
Recommended fuel	Unleaded	Unleaded	Diesel

BUSINESS PREFERRED NETWORK -

Each of the select dealerships in our Business Preferred Network (BPN) is committed to providing quality commercial-oriented products and service, as well as special financing and billing arrangements, to businesses that rely on Ford products. As a BPN customer, your business vehicles receive priority service at your BPN dealership to help get your vehicle back on the road quickly.



FINANCIAL SERVICES

Our commercial purchase plans and lines of credit offer attractive rates, negotiable terms and business-friendly options. If you prefer to lease, our CommerciaLeaseSM programs offer a wide variety of package options to meet your needs. For additional information, please visit our website at **www.fordcredit.com/comlend/**.



INTERIORS

		TAN
		MEDIUM FLINT
		XL/XLT/LARIAT
•	•	Oxford White
•		Arizona Beige Metallic
•	•	Red
•	•	Dark Toreador Red Metallic
•	•	Dark Green Satin Metallic
•	•	Medium Wedgewood Blue Metallic
•	•	True Blue Metallic
	•	Silver Metallic
	•	Dark Shadow Grey Metallic
•		Dark Stone Metallic
•	•	Black





Tan Vinyl

Medium Flint Vinyl





Tan Cloth

Medium Flint Cloth





Tan Vinvl Weave

Medium Flint Vinvl Weave





Tan Premium Cloth

Medium Flint Premium Cloth





Tan Leather

Medium Flint Leather

EXTERIORS



Oxford White



Arizona Beige Metallic



Red



Dark Toreador Red Metallic



Dark Green Satin Metallic



Medium Wedgewood Blue Metallic



True Blue Metallic



Silver Metallic



Dark Shadow Grey Metallic



Dark Stone Metallic



Black

Ford uses clearcoat paint for beauty and protection. Colors shown are representative only. Not all colors are available on all models. See your dealer for actual paint/trim options. Vehicles shown may contain optional equipment.



New Vehicle Limited Warranty

We want your Ford F-Series Chassis Cab ownership experience to be the best it can be. So under this warranty, your new vehicle comes with 3-year/36,000-mile Bumper-to-Bumper Coverage, 5-year/50,000-mile Safety Restraint Coverage, and 5-year/unlimited-mile Corrosion (Perforation) Coverage — all with no deductible. Please ask your Ford Dealer for a copy of this limited warranty.

For more assurance: There's now a 5-year/60,000-mile powertrain limited warranty that's fully transferable, has no deductible, and provides you with an additional 2 years or 24,000 miles of coverage; diesel engine warranty is 5 years/100,000 miles — on select components, including the engine and transmission — beyond the standard 3-year/36,000-mile Bumper-to-Bumper Coverage. Plus, Roadside Assistance is extended to 5 years or 60,000 miles, so you have the security of knowing that help may be only a phone call away should you run out of fuel, lock yourself out of the vehicle, or need towing. Your Ford Dealer can provide complete details on all of these advantages.



For a purchase or lease, the Ford **Extended Service Plan** (ESP) gives you "Peace-of-Mind" protection designed to cover key vehicle components and protect

you from the cost of unexpected repairs. Ask your dealer for an ESP, the only service contract backed exclusively by Ford and honored at all Ford dealerships.