

**LEGEND:** S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

**NOTE:** Information shown is correct at time of publication, and is subject to change without notice.

## 2007 Dodge Caliber FEATURE AVAILABILITY

	SE	SXT	R/T AWD	FWD
<b>EXTERIOR</b>				
<b>Badges</b>				
Caliber badge _____	S	S	S	S
Body color liftgate appliqué _____	S	S	S	S
SXT badge _____	—	S	—	—
R/T badge _____	—	—	S	S
All-wheel-drive badge _____	—	—	S	—
Black-out tape _____	—	P	S	S
Colors: Inferno Red Crystal Pearl Coat, Solar Yellow Clear Coat), Sunburst Orange Pearl Coat, Marine Blue Pearl Coat, Steel Blue Metallic Clear Coat, Bright Silver Metallic Clear Coat, Black Clear Coat, Stone White Clear Coat and Light Khaki Metallic Clear Coat _____	O	O	O	O
<b>Door Handles</b>				
Black door handles _____	S	S	—	—
Bright door handles _____	—	—	S	S
Body Color Fascias _____	S	S	S	S
Fixed Long Mast Antenna _____	S	S	S	S
<b>Grille</b>				
Body color grille _____	S	—	—	—
Chrome grille _____	—	S	S	S
<b>Lamps</b>				
Halogen headlamps _____	S	S	S	S
Fog lamps _____	—	O/P	S	S
Daytime running lamp system _____	O	O	O	O
<b>Mirrors</b>				
Manual _____	S	—	—	—
Power _____	P	S	S	S
<b>Moldings</b>				
Body color bodyside _____	S	S	—	—
Chrome bodyside _____	—	—	S	S
Sill molding _____	—	—	S	S
Rear Spoiler _____	S	S	S	S
Rear Window Defroster _____	S	S	S	S
Sunroof, power express open/close _____	—	O	O	O
<b>Windows</b>				
Manual _____	S	—	—	—
Solar control glass _____	S	S	S	S
Power windows, driver one-touch _____	P	S	S	S
<b>Wiper System</b>				
Windshield, variable, intermittent _____	S	S	S	S
Rear window wiper/washer _____	S	S	S	S

	SE	SXT	R/T	
			AWD	FWD
<b>INTERIOR</b>				
Air Conditioning _____	O	S	S	S
Interior Colors: Pebble Beige, Pastel Slate Gray _____	O	O	O	O
<b>Floor Covering</b>				
Carpet _____	S	S	S	S
Vinyl washable and removable load floor covering _____	S	S	S	S
<b>Console</b>				
Full-length floor _____	S	S	S	S
Illuminated cup holders _____	S	S	S	S
12V auxiliary power outlet _____	S	S	S	S
115V auxiliary power outlet _____	—	S	S	S
Color-keyed PRNDL bezel _____	—	P	S	S
Satin Silver PRNDL bezel _____	S	S	P	P
Sliding armrest with cell phone holder _____	S	S	S	S
Floor Mats, front and rear _____	O	S	S	S
<b>Instrument Cluster</b>				
Electroluminescent cluster _____	S	S	S	S
120 mph primary speedometer _____	S	S	S	S
Outside temperature gauge _____	S	S	S	S
<b>Instrument Panel</b>				
<i>Chill Zone</i> <sup>™</sup> instrument panel cooler _____	P	S	S	S
Satin Silver bezel _____	S	S	P	P
Color-keyed bezel _____	—	P	S	S
Chrome switches _____	—	S	S	S
<b>Lamps</b>				
Front dome lamp _____	S	—	—	—
Cargo compartment lamp _____	S	—	—	—
Map/dome reading lamps _____	—	S	S	S
Removable/rechargeable lamp _____	—	S	S	S
Illuminated entry _____	—	S	S	S
Passenger Assist Handles _____	—	S	S	S
<b>Mirrors</b>				
Rearview day/night mirror _____	S	S	S	S
Rearview Auto Dim mirror _____	—	P	P	P
<b>Seats</b>				
Cloth low-back bucket seats _____	S	S	—	—
Cloth seats with color-keyed insert _____	—	P	S	S
Fold-flat front passenger seat _____	—	S	S	S
Driver height adjuster seat _____	—	S	S	S
YES Essentials® cloth seats _____	—	O	O	O
Flexible seating group _____	—	S	S	S
Folding flat load floor storage _____	S	S	S	S
Heated front seats _____	—	O	O/P	O/P
Marine Blue seat insert _____	—	P	P	P
Inferno Red seat insert _____	—	P	P	P
Sunburst Orange seat insert _____	—	P	P	P
Leather-trimmed bucket seats _____	—	P	P	P
Manual driver lumbar adjust _____	—	P	P	P
Rear 60/40 split recline seat _____	—	S	S	S
<b>Sound System</b>				
AM/FM CD radio with auxiliary audio input jack _____	S	S	S	S
AM/FM CD six-disc with cassette and MP3 capability _____	O	O	O	O
AM/FM CD six-disc with Full Map GPS Navigation Radio (late availability) _____	O	O	O	O
SIRIUS Satellite Radio _____	O	O	O	O
One-year service provided by SIRIUS _____	P	P	P	P
<b>Speakers</b>				
Four speakers _____	S	S	S	S
MusicGate Power <sup>™</sup> nine-speaker Boston Acoustic premium sound system, with _____				

subwoofer and two articulating liftgate speakers _____	O	O	O	O
Speed Control _____	—	O	S	S
Steering, power rack and pinion _____	S	S	S	S
Steering, performance _____	—	—	S	S
Steering Column, tilt _____	S	S	S	S
Steering Wheel				
Leather-wrapped _____	—	P	S	S
Steering wheel-mounted audio controls (must have speed control) _____		P	S	S
Sun Visors, sliding with mirrors _____	S	S	S	S
Electronic Vehicle Information Center _____	—	P	P	P
Tonneau Cover _____	O	P	S	S
UConnect® Hands-free Communication System _____	—	O	O	O

SE SXT RT  
AWD FWD

### POWERTRAIN AND CHASSIS

#### Engines:

1.8-liter 4 cyl. DOHC 16v VVT _____	S	S	—	—
2.0-liter 4-cyl. DOHC 16V VVT _____	O	O	—	—
2.4-liter 4-cyl. DOHC 16V VVT _____	—	—	S	S

#### Transmissions

Five-speed manual T355 _____	S	S	—	S
Continuously Variable Transaxle II (CVT2) _____	O	O	S	O
Auto Stick automatic _____	—	—	S	—

#### Brakes

Power front disc/rear drum _____	S	S	—	—
Anti-lock front disc/rear drum _____	O	O/P	—	—
Anti-lock four-wheel disc _____	—	P	S	S
Brake Assist _____	—	P	P	P

#### Engine Block Heater \_\_\_\_\_

#### Engine Oil Cooler \_\_\_\_\_

#### Exhaust Tip, chrome \_\_\_\_\_

#### Fuel Tank

13.6 gal. _____	S	S	—	S
13.5 gal _____	—	—	S	—

#### Steering

Power, rack and pinion _____	S	S	—	—
Performance Steering _____	—	—	S	S

#### Suspension

Touring _____	S	S	—	—
Sport _____	—	—	S	S

#### Tires(a)

P205/70R15 BSW all-season _____	S	—	—	—
Dunlop brand tires _____	S	—	—	—
P215/60R17 BSW AS Touring _____	—	S	—	—
P215/55R18 BSW AS Performance _____	—	—	S	S
Firestone brand tires _____	—	S	S	S
Compact spare _____	S	S	S	S

#### Wheels

15 x 6.0 steel wheel _____	S	—	—	—
15" wheel covers _____	S	—	—	—
17 x 6.5 steel wheel _____	—	S	—	—
17" wheel covers _____	—	S	—	—
17 x 6.5 aluminum _____	—	O/P	—	—
18 x 7.0 aluminum _____	—	—	S	S
18 x 7.0 aluminum chrome clad _____	—	—	O	O

#### Trailer Tow Group \_\_\_\_\_

O O O O

(a) Another tire size or brand may also be used.

	SE	SXT	R/T	
			AWD	FWD
<b>SAFETY AND SECURITY</b>				
Air Bags				
Next generation multi-stage front air bags _____	S	S	S	S
Side window curtain front air bags _____	S	S	S	S
Side front seats air bags _____	O	O	O	O
Electronic Stability Program _____	—	O	O	O
Locks				
Manual locks _____	S	—	—	—
Speed sensitive power locks, includes liftgate _____	P	S	S	S
Occupant Classification System _____	S	S	S	S
Power Accessory Delay _____	S	S	S	S
Remote Keyless Entry _____	P	S	S	S
Security Alarm _____	—	P	P	P
Sentry Key® Engine Immobilizer _____	S	S	S	S
Tire Pressure Monitoring System _____	—	P	P	P
Universal Door Opener _____	—	P	P	P

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

(b) Always sit properly in the seat with the seat belt fastened. Always observe the passenger air bag indicator lamp to determine if the OCS classification is appropriate. Children 12 and under should always be in a back seat correctly using an infant or child restraint system or the seat belt positioned correctly for the child's age and weight.

	SE	SXT	R/T	
			AWD	FWD
<b>EQUIPMENT GROUPS</b>				
P1 – Driver Convenience Group includes compass and temperature gauge, universal garage door opener, electrochromic mirror, outside temperature gauge and tire pressure monitor _____	—	O	O	O
P2 – Leather Interior Group includes leather seats, heated front seats, leather-wrapped steering wheel and manual lumbar adjuster _____	—	O	O	O
P3 – Power Equipment Group includes driver one-touch power window, power locks, remote keyless entry and power mirrors _____	O	O	S	S
P4 – Security Group includes tonneau cover, security alarm and air filtration system _____	—	O	O	O
P5 – Sport Appearance Interior Group includes Pastel Slate Gray color with Red, Orange or Blue seat inserts that coordinate with the Exterior color, center stack and shifter bezels; cloth seats with colored Inserts, color-keyed PRNDL and IP bezels _____	—	O	S	S
P6 – Sport Package includes fog lamps, 17-inch aluminum wheels and Sport Appearance Package _____	—	P	S	S

## SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

### General Information

Body Style \_\_\_\_\_ Sports Tourer  
 Assembly Plant \_\_\_\_\_ Belvidere, Illinois  
 EPA Vehicle Class \_\_\_\_\_ Compact car  
 Introduction Date \_\_\_\_\_ January 2006, as 2007 model

### Engine: 1.8-Liter DOHC 16-Valve I4 with DUAL VVT

Availability \_\_\_\_\_ Standard—SE and SXT  
 Type and Description \_\_\_\_\_ Four cylinders in line, tuned intake manifold with Electronic Active Charge Motion Control valves  
 Displacement \_\_\_\_\_ 109.7 cu. in. (1798 cu cm)

Bore x Stroke \_\_\_\_\_ 3.38 x 3.05 (86 x 77.4)  
 Valve System \_\_\_\_\_ Chain-driven DOHC, 16 valves,  
 electronically controlled dual Variable Valve Timing,  
 direct-acting shimless mechanical bucket tappets  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
 Construction \_\_\_\_\_ High-pressure die-cast aluminum block with dry iron liners,  
 cast-aluminum cylinder head, cast-aluminum ladder frame  
 forged steel crankshaft  
 Compression Ratio \_\_\_\_\_ 10.5:1  
 Power (SAE net, estimated) \_\_\_\_\_ 148 bhp (110 kW) @ 6,500 rpm (79.4 bhp/liter)  
 Torque (SAE net, estimated) \_\_\_\_\_ 125 lb.-ft. (169 N•m) @ 5,200 rpm  
 Max. Engine Speed \_\_\_\_\_ 6,750 rpm (electronically limited)  
 Fuel Requirement \_\_\_\_\_ Unleaded regular, 87 octane (R+M)/2  
 Oil Capacity \_\_\_\_\_ 5.0 qt. (4.7L) SAE 5W/20  
 Coolant Capacity \_\_\_\_\_ 7.2 qt. (6.8L)  
 Emission Controls \_\_\_\_\_ Single catalytic converter,  
 dual heated oxygen sensors and engine features  
 Smog-forming Pollution \_\_\_\_\_ 0.9 g/mile (0.56 g/km)<sup>(a)</sup>  
 Max. Gross Trailer Weight \_\_\_\_\_ 1,000 lbs. (450 kg)  
 Estimated EPA Fuel Economy  
 MPG (City/Hwy) \_\_\_\_\_ 28/32  
<sup>(a)</sup> NMOG + NOx emission limits under ULEV II and Tier 2, Bin 5 emission requirements.

**Engine: 2.0-Liter DOHC 16-Valve I4 with DUAL VVT**

Availability \_\_\_\_\_ Optional – SE and SXT  
 Type and Description \_\_\_\_\_ Four cylinders in line, tuned intake manifold  
 with electronic Active Charge Motion Control valves,  
 dual counter-rotating balance shafts  
 Displacement \_\_\_\_\_ 121.9 cu. in. (1998 cu cm)  
 Bore x Stroke \_\_\_\_\_ 3.39 x 3.39 (86 x 86)  
 Valve System \_\_\_\_\_ Chain-driven DOHC, 16 valves,  
 electronically controlled dual Variable Valve Timing,  
 direct-acting shimless mechanical bucket tappets  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
 Construction \_\_\_\_\_ High-pressure die cast aluminum block with dry iron liners,  
 cast-aluminum cylinder head, cast-aluminum ladder frame,  
 Forged steel crankshaft  
 Compression Ratio \_\_\_\_\_ 10.5:1  
 Power (SAE net, estimated) \_\_\_\_\_ 158 bhp (117 kW) @ 6,400 rpm (79 bhp/liter)  
 Torque (SAE net, estimated) \_\_\_\_\_ 141 lb.-ft. (191 N•m) @ 5,000 rpm  
 Max. Engine Speed \_\_\_\_\_ 6,750 rpm (electronically limited)  
 Fuel Requirement \_\_\_\_\_ Unleaded regular, 87 octane (R+M)/2  
 Oil Capacity \_\_\_\_\_ 5.0 qt. (4.7L) SAE 5W/20  
 Coolant Capacity \_\_\_\_\_ 7.2 qt. (6.8L)  
 Emission Controls \_\_\_\_\_ Single catalytic converter,  
 dual heated oxygen sensors and engine features  
 Smog-Forming Pollution \_\_\_\_\_ 0.9 g/mile (0.56 g/km)<sup>(a)</sup>  
 Max. Gross Trailer Weight \_\_\_\_\_ 1,000 lbs. (450 kg) std., TBD with Trailer Tow Group<sup>b</sup>  
 Estimated EPA Fuel Economy  
 MPG (City/Hwy) \_\_\_\_\_ 26/30  
<sup>(a)</sup> NMOG + NOx emission limits under ULEV II and Tier 2, Bin 5 emission requirements.  
<sup>(b)</sup> Not determined as of publication time.

**Engine: 2.4-Liter DOHC 16-Valve I4 with DUAL VVT**

Availability \_\_\_\_\_ Standard—R/T FWD and AWD  
 Type and Description \_\_\_\_\_ Four cylinders in line, tuned intake manifold with  
 Electronic Active Charge Motion Control valves  
 dual counter-rotating balance shafts  
 Displacement \_\_\_\_\_ 144 cu. in. (2360 cu cm)  
 Bore x Stroke \_\_\_\_\_ 3.46 x 3.82 (88 x 97)

Valve System \_\_\_\_\_ Chain-driven DOHC, 16 valves,  
electronically controlled dual Variable Valve Timing,  
direct-acting shimless mechanical bucket tappets

Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless

Construction \_\_\_\_\_ High-pressure die-cast aluminum block with dry iron liners,  
cast-aluminum cylinder head, cast-aluminum ladder frame,  
forged steel crankshaft

Compression Ratio \_\_\_\_\_ 10.5:1

Power (SAE net, estimated) \_\_\_\_\_ 172 bhp (128 kW) @ 6,000 rpm (72 bhp/liter)

Torque (SAE net, estimated) \_\_\_\_\_ 165 lb.-ft. (223 N•m) @ 4,400 rpm

Max. Engine Speed \_\_\_\_\_ 6,500 rpm (electronically limited)

Fuel Requirement \_\_\_\_\_ Unleaded regular, 87 octane (R+M)/2

Oil Capacity \_\_\_\_\_ 5.0 qt. (4.7L) SAE 5W/20

Coolant Capacity \_\_\_\_\_ 7.2 qt. (6.8L)

Emission Controls \_\_\_\_\_ Single catalytic converter, FWD,  
Dual catalytic converter, AWD,  
Dual heated oxygen sensors and engine features

Smog-Forming Pollution \_\_\_\_\_ 0.9 g/mile (0.56 g/km)<sup>(a)</sup>

Max. Gross Trailer Weight \_\_\_\_\_ 1,000 lbs. (450 kg)/2000 lbs. (900 kg) with Trailer Tow Group

Estimated EPA Fuel Economy

MPG (City/Hwy) \_\_\_\_\_ 26/30—FWD w/ 5-speed manual transaxle  
\_\_\_\_\_ 24/27—FWD with CVT  
\_\_\_\_\_ 23/26—AWD with CVT

<sup>(a)</sup> NMOG + NOx emission limits under ULEV II and Tier 2, Bin 5 emission requirements.

**Transaxle: Manual, Magna Driveline T355 5-Speed**

Availability \_\_\_\_\_ Standard SE and SXT with 1.8L

Description \_\_\_\_\_ 5-speed, overdrive, synchronized in all forward ratios,  
cable-operated, 3-plane shifter

**Gear Ratios**

1 <sup>st</sup>	_____	3.77
2 <sup>nd</sup>	_____	2.16
3 <sup>rd</sup>	_____	1.41
4 <sup>th</sup>	_____	1.026
5 <sup>th</sup>	_____	0.81
Reverse	_____	3.417
Final Drive Ratio	_____	4.12
Overall Top Gear	_____	3.34

**Transmission: Automatic, CVT2**

Availability \_\_\_\_\_ Standard with 2.0L and available 2.4L NAFTA markets

Description \_\_\_\_\_ Continuously variable ratio, lock-up torque converter, electronic controls

**Gear Ratios**

Forward	_____	2.349:1 to 0.394:1 continuously variable
Reverse	_____	1.762:1
Final Drive Ratio	_____	6.12:1
Overall Top Gear Ratio	_____	2.411

**Drivetrain**

**Front-wheel Drive**

Availability \_\_\_\_\_ Standard

**All-wheel Drive**

Availability \_\_\_\_\_ Optional with 2.4L engine

Type \_\_\_\_\_ Electromagnetically Controlled Coupling (ECC) with variable torque output

Rear Differential \_\_\_\_\_ Open



Steering Turns (lock-to-lock) \_\_\_\_\_ All-wheel drive—37.2 ft (11.3 m)  
15- or 17-inch wheels and tires—2.88  
18-inch wheels and tires—2.76

**Tires<sup>a</sup>**

Availability \_\_\_\_\_ SE  
Size and Type \_\_\_\_\_ P205/70R15 all-season  
Mfr. and Model \_\_\_\_\_ Dunlop SP50  
Revs per Mile (km) \_\_\_\_\_ 801 (1289)

Availability \_\_\_\_\_ SXT  
Size and Type \_\_\_\_\_ P215/60R17 BSW AS Touring  
Mfr. and Model \_\_\_\_\_ Firestone Affinity S3  
Revs per Mile (km) \_\_\_\_\_ 760 (1223)

Availability \_\_\_\_\_ R/T  
Size and Type \_\_\_\_\_ P215/55R18 AS Performance  
Mfr. and Model \_\_\_\_\_ Firestone Firehawk GTA 03  
Revs per Mile (km) \_\_\_\_\_ 765 (1231)

**WHEELS**

Availability \_\_\_\_\_ Standard SE  
Type and Material \_\_\_\_\_ Stamped steel w/five-spoke wheel covers  
Size \_\_\_\_\_ 15 x 6.0

Availability \_\_\_\_\_ Standard SXT  
Type and Material \_\_\_\_\_ Stamped steel w/five-spoke wheel covers  
Size \_\_\_\_\_ 17 x 6.5

Availability \_\_\_\_\_ Optional SXT  
Type and Material \_\_\_\_\_ Machine-faced aluminum  
Size \_\_\_\_\_ 17 x 6.5

Availability \_\_\_\_\_ Standard R/T  
Type and Material \_\_\_\_\_ Machine-faced aluminum  
Size \_\_\_\_\_ 18 x 7.0

Availability \_\_\_\_\_ Optional R/T  
Type and Material \_\_\_\_\_ Chrome-clad aluminum  
Size \_\_\_\_\_ 18 x 7.0

(a) Other sizes and brands may also be used

**Brakes**

Availability \_\_\_\_\_ Standard SE

Front

Size and Type \_\_\_\_\_ 10.8 x 1.0 (276 x 26) vented disc  
with 2.2 (57) single-piston floating caliper  
Swept Area<sup>a</sup> \_\_\_\_\_ 205.36 sq. in. (1325.12 sq. cm)

Rear

Size and Type \_\_\_\_\_ 9.0 x 1.38 (229 x 35) drum  
Swept Area \_\_\_\_\_ 78.1 sq. in. (503.6 sq. cm)

Power Assist Type \_\_\_\_\_ 10 (254) single-vacuum diaphragm  
Four-Wheel Anti-Lock \_\_\_\_\_ Opt.—Included with CVT transmission

Availability \_\_\_\_\_ Standard SXT

Front

Size and Type \_\_\_\_\_ 11.5 x 1.0 (294 x 26) vented disc  
with 2.2 (57) single-piston floating caliper  
Swept Area \_\_\_\_\_ 223.52 sq. in. (1442.12 sq. cm)

Rear

Size and Type \_\_\_\_\_ 9.0 x 0.85 (229 x 35) drum  
Swept Area \_\_\_\_\_ 78.1 sq. in. (503.6 sq. cm)



Power Assist Type \_\_\_\_\_ 10 (254) single-vacuum diaphragm  
Four-Wheel Anti-Lock \_\_\_\_\_ Opt.—Included with CVT transmission

Availability \_\_\_\_\_ Standard R/T  
Front

Size and Type \_\_\_\_\_ 11.5 x 1.0 (294 x 26) vented disc  
with 2.2 (57) single-piston floating caliper

Swept Area \_\_\_\_\_ 223.52 sq. in. (1442.12 sq. cm)

Rear

Size and Type \_\_\_\_\_ 10.3 x 1.39 (262 x 10) solid disc  
with 1.4 (35) single-piston floating caliper

Swept Area \_\_\_\_\_ 138.64 sq. in. (894.6 sq. cm)

Power Assist Type \_\_\_\_\_ 10 (254) single-diaphragm vacuum

Four-wheel Anti-lock \_\_\_\_\_ R/T

Electronic Stability Program<sup>(b)</sup> \_\_\_\_\_ Optional SXT, R/T

(a) Note: Per axle

(b) Late Availability